

## ERRATUM

# Investigating the influence of the operating frequency on the gas phase emitter effect of dysprosium in ceramic metal halide lamps

To cite this article: J Reinelt *et al* 2011 *J. Phys. D: Appl. Phys.* **44** 299601

View the [article online](#) for updates and enhancements.

## You may also like

- [Influence of the excitation frequency on the RF power transfer efficiency of low pressure hydrogen ICPs](#)  
D Rauner, S Briefi and U Fantz
- [Low terahertz frequency on-chip multi-functional modulator with amplitude and phase modulation](#)  
Huajie Liang, Hongxin Zeng, Hanyu Zhao et al.
- [The effects of the driving frequencies on micro atmospheric pressure He/N<sub>2</sub> plasma jets driven by tailored voltage waveforms](#)  
G Hübner, L Bischoff, I Korolov et al.



**ECS**  
The  
Electrochemical  
Society  
Advancing solid state &  
electrochemical science & technology

**DISCOVER**  
how sustainability  
intersects with  
electrochemistry & solid  
state science research

# Erratum

**Investigating the influence of the operating frequency on the gas phase emitter effect of dysprosium in ceramic metal halide lamps**

J Reinelt, M Westermeier, C Ruhrmann, A Bergner,

G M J F Luijks, P Awakowicz and J Mentel

2011 *J. Phys. D: Appl. Phys.* **44** 224006

Received 3 June 2011

Published 30 June 2011

On page 4 in the second paragraph, the first sentence should read:

The delay time of the current source, which is realized by an electronic device, varies so much in dependence on the operating parameters that the ‘sync’ output of the signal generator, by which the current source is controlled, is unsuitable to provide an appropriate trigger pulse.