# PAPER • OPEN ACCESS

# Investigation on the Precision Loss of Ball Screw Considering the Full Ball Load Distribution

To cite this article: Jiajia Zhao et al 2018 IOP Conf. Ser.: Mater. Sci. Eng. 422 012021

View the article online for updates and enhancements.

# You may also like

- <u>A novel self-powered MR damper:</u> <u>theoretical and experimental analysis</u> Guan Xinchun, Huang Yonghu, Ru Yi et al.
- <u>Remaining useful life prediction of ball</u> <u>screw based on integrating preload and</u> <u>precision</u> Yishen Zhang, Changguang Zhou, Conghui Nie et al.
- Investigation of The Reliability and Sensitivity of the Wear Resistance of Ball Screws Chang-Guang Zhou, Jing-Yao Xi, Bin-Bin Chen et al.





DISCOVER how sustainability intersects with electrochemistry & solid state science research



This content was downloaded from IP address 3.14.253.221 on 05/05/2024 at 05:15

# **Investigation on the Precision Loss of Ball Screw Considering** the Full Ball Load Distribution

Jiajia Zhao<sup>1,a</sup>, Mingxing Lin<sup>1,b</sup>, Xianchun Song<sup>2,c</sup>, Hongkui Jiang<sup>2,d</sup>, Xiaojian Wu<sup>1,e</sup>

<sup>1</sup>National Demonstration Center for Experimental Mechanical Engineering Education (Shandong University), Key Laboratory of High-efficiency and Clean Mechanical Manufacture of Ministry of Eduction, School of Mechanical Engineering, Shandong University, Jinan, Shandong, 250061, China

<sup>2</sup>Key Laboratory of Mechanical Engineering Innovation Technology, School of Mechanical and Electrical Engineering, Shandong Jianzhu University, Jinan, Shandong, 250101, China

E-mail: <sup>a</sup>zhaojia0922@126.com, <sup>b</sup>mxlin@sdu.edu.cn, <sup>c</sup>songxch@sdu.edu.cn, <sup>d</sup>jhk\_2001@sdjzu.edu.cn, <sup>e</sup>xjwu@sdu.edu.cn

Abstract: Ball screws are the driving functional components most frequently used for the machining equipments. However, the precision positioning error of ball screws decide directly machining accuracy of machine tools. This paper aims to investigate the precision loss of ball screw considering full ball load distribution. The raceway wear model is built to predict the precision loss of ball screw in different structural parameters and operating parameters. Meanwhile, the precision loss rate is obtained and analyzed during the whole running life.

### **1. Introduction**

With the development of high speed cutting, the dynamic performance of ball screw is getting higher and higher. As in many mechanisms, the wear in ball screws complicates the control design progress and reduces the positioning accuracy significantly. Lin [1] investigated the quasi-static contact characteristics of ball screw. Yoshida T [2] established a new finite element model to study the uneven distribution of stress. Mei [3] studied the influence of geometrical random error on the load distribution of ball screw. C. Braccesi [4] presented a general elastic plastic approach to impact analysis for stress state limit evaluation in ball screw bearings return system. Song [5] established a new online measuring system of ball screw movement precision. With the wear of ball screw, the accuracy of ball screw is reduced rapidly, which directly affects the life and the reliability of machine tool. A new model is built to predict the precision loss rate in different structural parameters and operating parameters.

# 2. Theoretical analysis

#### 2.1 The load distribution of the full ball

The contact deformation  $\delta$  between the ball and the nut or the screw are expressed as follows:

$$\delta_{ji} = C_j \cdot Q_i^{\frac{2}{3}}.$$
 (1)

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

 $\delta_{ji}(j=s \text{ or } n)$  are the contact deformation between the *i*th ball and the screw or the nut respectively,  $C_j$  (*j=s or n*) are the contact stiffness of the screw or the nut respectively,  $Q_i$  is the normal load between the *i*th ball and the raceway. The axial deformation of the screw or the nut can be obtained respectively.

$$\varepsilon_{ji} = \frac{F_{i-1,i} \cdot \Delta L}{E \cdot A_i} \quad , \quad \Delta L = l_p / N'.$$
<sup>(2)</sup>

 $\varepsilon_{ji}$  (*j*=*s* or *n*) are the axial deformation of the screw segment or the nut segment between the *i*-1 ball and the *i* ball, *E* is the elastic modulus of the screw and the nut,  $A_j$  (*j*=*s* or *n*) are the cross-sectional area of the screw or the nut in the contact point,  $\Delta L$  is the axial distance between two adjacent ball,  $F_{i-1,i}$  is the axial load of the screw segment between the *i*-1 th ball and the *i*th ball.  $l_P$  is the lead of the screw, N' is the number of balls in a single lead. Where the axial force relation of the screw along the axis is shown in Fig.1.

$$\xrightarrow{F_a} \xrightarrow{F_1} \xrightarrow{F_2} \xrightarrow{F_3} \xrightarrow{F_4} \xrightarrow{F_{i-1}} \xrightarrow{F_i} \xrightarrow{F_i}$$

Figure 1. The axial force diagram of the screw axis

Where  $F_a$  is the axial load,  $F_i$  is the axial force between the *i*th ball and the raceway. The relation of the axial force at each contact point can be obtained as follows:

$$F_{i-1,i} = F_a - \sum_{j=1}^{i-1} F_j = \sum_{j=1}^{N} F_j - \sum_{j=1}^{i-1} F_j = \sum_{j=i}^{N} F_j, \quad F_i = Q_i \cdot \sin\alpha \cdot \cos\lambda.$$
(3)

Where *N* is the number of ball,  $\alpha$  is the contact angle between the ball and the raceway,  $\lambda$  is the nominal helix angle of the screw. The deformation relation of ball screw between the *i*-1 ball and the *i* ball is shown in Fig.2.  $\delta_{jai\cdot l}$  and  $\delta_{jai}$  are the axial component of the Hertz contact deformation of the *i*-1 th ball and the *i*th ball with the nut raceway or the screw raceway respectively (*j*=*s* or *n*). The deformation coordination relationship can be obtained as follows:

$$\varepsilon_{si} + \varepsilon_{ni} = (\delta_{sai-1} - \delta_{sai}) + (\delta_{nai-1} - \delta_{nai}). \tag{4}$$



Figure 2. The deformation diagram of ball screw.

The axial component of the Hertz contact deformation between the ball and the nut raceway or the screw raceway can be obtained as follows [6]

$$\delta_a = \delta \sin \alpha \cdot \cos \alpha \tag{5}$$

By substituting (1), (2), (3) and (5) into (4), the iterative formula of full ball load distribution can be obtained as follows:

$$\begin{cases} Q_i^{\frac{2}{3}} - Q_{i-1}^{\frac{2}{3}} + \frac{\Delta L}{E} \cdot \left(\frac{1}{A_s} + \frac{1}{A_n}\right) / (C_s + C_n) \sum_{j=i}^N Q_j = 0 \\ F_a = \sum_{i=1}^N Q_i \cdot \sin \alpha \cdot \cos \lambda \end{cases}$$
(6)

#### 2.2 The wear model of the ball-screw contacts

Based on the Archard theory, the precision loss of the ball screw in the wear can be expressed as follows [7]

$$W_{ji} = K \frac{Q_i L_j}{H}.$$
(7)

Where  $W_{ji}$  (*j*=*s* or *n*) is the amount of wear volume,  $Q_i$  is the normal pressure of *i*th ball contact point,  $L_j$  is the relative sliding distance between ball and raceway at contact points, *K* is the coefficient of wear, *H* is the hardness of raceway. The contact area of ball with the screw or the nut can be written as follows:

$$A_{ji} = \pi a_{ji} \cdot b_{ji}. \tag{8}$$

Where  $a_{ji}$  and  $b_{ji}$  are the semi-major axis and semi-minor axis on the contact ellipse respectively. Considerating to the period of a ball passing through the contact point on the raceways of the screw or the nut, the coefficient  $f_{s_i}$ ,  $f_n$  is introduced respectively. Thus, the total sliding distance of a contact

point on the raceways of the screw or the nut can be obtained as follows:  

$$L_{s} = f_{s} \cdot \left| \overrightarrow{V_{s}} \right| t = \frac{b_{s} \sin \lambda}{l_{s}} \cdot \left| \overrightarrow{V_{s}} \right| t, \quad L_{n} = f_{n} \cdot \left| \overrightarrow{V_{n}} \right| t = \frac{b_{n} \sin \lambda}{ml_{p}} \cdot \left| \overrightarrow{V_{n}} \right| t.$$
(9)

Where *t* is the running time,  $l_s$  is the effective travel of the screw, *m* is the number of turns in one chain and  $V_j$  (*j*=*s* or *n*) are the ball's slipping velocity relative to the raceway at the contact point between a ball and the screw or the nut respectively.

By combining (7), (8), (9) and (10), the wear depth of the raceway can be obtained as follows:

1 ....

1 .1

$$\Delta \delta_{a} = \sum_{i=1}^{N} \frac{W_{si}}{A_{si}} + \sum_{i=1}^{N} \frac{W_{ni}}{A_{ni}} = \sum_{i=1}^{N} \left( \frac{K_{s}Q_{i}\sin\lambda \left|V_{s}\right|}{\pi Ha_{s}I_{s}} + \frac{K_{n}Q_{n}\sin\lambda \left|V_{n}\right|}{\pi Ha_{n}mL_{p}} \right) \cdot t = \delta_{wt} \cdot t.$$

$$\tag{10}$$

Where  $\delta_{wt}$  is the precision loss rate of ball screw.

Table 1. Parameters used in the simulation test

Parameters	Value	Unit	
Nominal diameter	40	mm	
Ball diameter	4.763	mm	
Lead angle	3.64	0	
Lead	8	mm	
Rows ×Turns	3x1		
Contact angle	45	0	
Poisson's ratio	0.3		
Young's modulus	205	GPa	

## **3. Results and discussion**

It is worth mentioning that the running-in process is ignored in this paper to study the precision loss of ball screw because of wear. The precision loss rate of ball screw versus axial load in different rotational speeds are shown in Fig.3. The relation of precision loss rate versus the axial load and rotational speed can be described as syntagmatic spatial plane. The precision loss rate is increased with an increasing axial load and rotational speed. When the axial load is increased, the normal force and the contact ellipse area between the ball and the raceway increase with the increasing axial load. However, the increasing rate of contact normal force is larger than the increasing rate of contact

#### 2018 International Conference on Smart Materials Applications

IOP Conf. Series: Materials Science and Engineering 422 (2018) 012021 doi:10.1088/1757-899X/422/1/012021

deformation area. It is obvious that the precision loss rate is proportional to the normal force and inversely proportional to the contact area. Thus, for a given rotational speed, the precision loss rate increases with increasing axial load. For a given axial load, the precision loss rate increases with increasing rotational speed.



Figure3. Precision loss rate of the raceway versus axial load at different rotational speeds

Fig.4 show the precision loss rate of ball screw in different structure parameters. The precision loss rate of ball screw decreases with the increase of the contact angle. Thus, the greater contact angle can reduces the precision loss of ball screw. In addition, The precision loss rate of ball screw increases with the increase of the helix angle. Thus, the precision loss of large lead ball screw is serious, and properly reducing helix angle can decrease the precision loss of ball screw. The precision loss rate of ball screw increases with the increase of the raceway radius. While, the precision loss rate of ball screw decreases with the increase of ball diameter. The turning point is the situation that the ball radius is equal to the raceway radius. Therefore, It's obvious that reasonable structure parameters can improve the precision preservation of ball screw.





**Figure 4.** Precision loss rate of the raceway in different structure parameters, (a) contact angle, (b) helix angle, (c) raceway radius and (d) ball diameter.

# 4. Conclusion

High-precision machine tools can not be separated from high-precision functional components. As a key functional component, the accuracy of ball screw directly affects the positioning precision of machine tools. The wear model is built to predict the precision loss of the ball screw in different structural parameters and operating parameters. Meanwhile, the precision loss rate is obtained and analyzed during the whole running life.

#### 5. Acknowledgement

This work was supported by the National Natural Science Foundation of China (51475267).

#### 6. References

- [1] M. C. Lin, Design and mechanics of the ball screw mechanism. *The University of Wisconsin-Madison*, (1989).
- [2] Yoshida T., Tozaki Y., Study on load distribution and motion of ball screws. *Journal of Japanese Society of tribologists*, Vol. 8 (2003), p.659-666.
- [3] X.S. Mei, Study on the load distribution of ball screw with error. *Mechanism and Machine Theory*, Vol. 38 (2003), p.1257-1269.
- [4] C. Braccesi, L. Landi, A general elastic plastic approach to impact analysis for stress state limit evaluation in ball screw bearings return system. *International Journal of Impact Engineering*, Vol. 34 (2007), p.1272-1285.
- [5] Xianchun Song, Yuankai Lu, Screw motion precision on-line measurement system design and experimental analysis. *Journal of Shandong Jianzhu University*, Vol. 35 (2017), p.409-413.
- [6] Hertz H., On the contact of elastic solids, *Journal F ür die Reine und Angewandte Mathematik*, Vol. 92 (1881), p.156-171.
- [7] Zhou C.G., Ou Y. and Feng H.T., Investigation of the precision loss for ball screw raceway based on the modified Archard theory, *Industrial Lubrication and Tribology*, Vol.2 (2017), p.166-173.