PAPER

Egg white based biological microlasers

To cite this article: Toan Van Nguyen et al 2020 J. Phys. D: Appl. Phys. 53 445104

View the article online for updates and enhancements.

You may also like

- III–V microdisk/microring resonators and injection microlasers
 Natalia Kryzhanovskaya, Alexey Zhukov, Eduard Moiseev et al.
- <u>Magnetic nanoparticles embedded in</u> <u>microlasers for controlled transport in</u> <u>different sensing media</u> Hanh Hong Mai, Van Huy Hoang, Manh Quynh Luu et al.
- Physicochemical characteristics of egg white powder using Lactobacillus bulgaricus
 N F N Azizah, H Evanuarini and E S Widyastuti





DISCOVER how sustainability intersects with electrochemistry & solid state science research



This content was downloaded from IP address 18.116.51.117 on 25/04/2024 at 14:36

J. Phys. D: Appl. Phys. 53 (2020) 445104 (6pp)

Egg white based biological microlasers

Toan Van Nguyen^{1,2}, Hanh Hong Mai², Thuong Van Nguyen³, Dung Chi Duong⁴ and Van Duong Ta⁴

¹ Department of Physics, Le Quy Don Technical University, 236 Hoang Quoc Viet, Hanoi 100000, Vietnam

² Department of Quantum Optics, Faculty of Physics, University of Science, Vietnam National University,
334 Nguyen Trai, Hanoi 100000, Vietnam

³ Institute of Technical Physics, Military Science and Technology Academy, 17 Hoang Sam, Hanoi 100000, Vietnam

⁴ Department of Optical Devices, Le Quy Don Technical University, 236 Hoang Quoc Viet, Hanoi 100000, Vietnam

E-mail: duong.ta@mta.edu.vn

Received 14 April 2020, revised 8 June 2020 Accepted for publication 11 June 2020 Published 5 August 2020



Abstract

Biolasers made of biological materials hold great potential for implantable biosensing and cell-tracking. However, the current bio-extracted materials used for biolasers generally require a complicated synthesis process and therefore suffer from high cost. In this work, we demonstrate that low-cost natural egg white is an excellent biomaterial for a laser cavity. Using a simple dehydration method, dye-doped goose egg white microspheres are obtained with various sizes from 20 to 160 μ m in diameter. These microspheres can act as excellent laser sources under optical excitation with lasing threshold of ~26 μ J mm⁻² and quality (Q) factor up to 3 × 10³. The lasing mechanism is studied and ascribed to the whispering gallery mode. Size-dependence of the lasing spectrum and Q factor are also investigated. Owing to the ease of fabrication, the cost-effectiveness, goose egg white based microlasers are promising for biosensing and bioimaging applications.

Keywords: biolasers, microlasers, whispering gallery mode, egg white

(Some figures may appear in colour only in the online journal)

1. Introduction

Biolasers whose gain medium and/or cavity made of biological materials have potential for cell-tracking, bioimaging and next generation biosensing applications [1-4]. Research on biolasers started five decades ago when Hansch utilized gelatin (a protein produced by the hydrolysis of collagen) as a laser cavity [5]. To date, various bio-extracted materials have been explored for biolasers, such as DNA, bovine serum albumin (BSA), silk fiborin, green fluoresecent protein (GFP) [6–10]. GFP can be used as a gain material while the other materials are used for a cavity matrix. However, these biomaterials often require complicated synthesis and therefore are processed with a high cost [11].

To compensate the high cost of bio-extracted materials, several ideas have been proposed with promising results such as the use of biocompatible synthetic polyvinyl alcohol (PVA) [12] or natural materials like starch from a potato as a laser cavity [13]. Regarding these two materials, starch is of a lower cost and always available. However, starch also has some drawbacks, such as poor mechanical properties and medium optical transparency, which would affect the quality of laser cavities [14, 15]. As a result, exploring other alternative natural biomaterials that are appropriate for biolasers is highly necessary.

Egg white (EW) is a natural biomaterial that has been used as a common nutritious food for a long time, but it has not been explored for biolasers. Compared with BSA protein and PVA polymer, EW is supposed to have lower cost and be easier to access. In general, EW is composed of 88.5% water and 10.5% protein (including ovalbumin, lysozyme, ovotransferrin, ovomucin) and demonstrates antimicrobial activities [16–19]. Furthermore, ovalbumin, the main protein of EW, has a high refractive index, about 1.55 at 600 nm [20], which is higher than that of PVA (around 1.45) [12] and starch polymer (1.53) [21]. As a result, EW can have a high refractive index which is crucial for making high-quality (Q) factor cavities [20, 22].

In this work, we demonstrate, for the first time, the use of goose egg white (GEW) as a novel material for biolasers. By using a simple fabrication technique, dye-doped GEW microspheres are obtained. Under optical pulse excitation, these microspheres emit lasing emission with excellent properties.

2. Materials and methods

2.1. Preparing aqueous dye-doped egg white solution

A goose egg was purchased just one day after being laid. GEW was chosen for the laser cavity because it has higher transparency compared with that of other eggs, such as a chicken egg. GEW was separated from the yolk using a stainless steel sieve (figure 1(a)). Then, dye-doped GEW solution was prepared by magnetically stirring (for 5 min, at room temperature) a mixture that contains 3 ml GEW and 1 ml aqueous solution 2.5 wt% of rhodamine B (RhB, >95% dye, from Sigma-Aldrich).

2.2. Fabrication of microsphere biolasers from dye-doped egg white solution

Dye-doped GEW microspheres were fabricated by dehydration in a solvent [23] as shown in figure 1(b) [24]. Firstly, 5 ml of 1-decanol (>99% purity, from Sigma-Aldrich) was poured into a glass beaker where a Teflon substrate was placed at the bottom. The hydrophobicity of Teflon keeps droplets in spherical shapes which is vital for the formation of solid microspheres. Secondly, a micropipette was used to create a droplet (containing dye-doped GEW solution) on the Teflon substrate immersed in 1-decanol. Next, the droplet was dispersed into smaller droplets, so-called microdroplets, by using a tiny needle. As 1-decanol is immiscible in water, these microdroplets are self-assembled on the Teflon substrate by surface tension. To increase the dehydration rate of water from microdroplets into 1-decanol, the whole mixture was heated to about 80 °C and keep at this temperature for 6 min. This process dehydrates all water molecules from the microdroplets and leads to the formation of solid microspheres (figure 1(b)). Finally, the obtained microspheres were taken out and subsequently heated at 100 °C for 4 min to completely remove the 1-decanol on their surface. After cooling down to room temperature, these microspheres are ready for optical characterizations. In addition, as EW-based microspheres have been used for drug delivery [25], the current fabriation technology may also be applied for this kind of application.

2.3. Optical characterizations

We used a micro-photoluminescence (μ -PL) setup to study dye-doped GEW microspheres. The pumping source was a Nd:YAG nanosecond pulse laser (Litron Lasers) with a wavelength of 532 nm, a repetition rate of 10 Hz and a pulse duration of 7 ns. The microspheres were excited by a focus laser beam with the spot size of \sim 350 μ m in diameter. Emission from the microspheres was collected by a 10 × objective and subsequently delivered to an AvaSpec-2048L (Avantes) for spectral recording. The spectral resolution is \sim 0.2 nm. All optical characterizations were carried out in the ambient air and at room temperature.

3. Results and discussion

3.1. Dye-doped egg white microspheres

Figure 2 shows the optical microscope and scanning electron microscope (SEM) images of dye-doped EW microspheres with a diameter from about 20 to 160 μ m. From the optical microscope (figure 2(a)), it can be seen that all microspheres exhibit a round shape with a uniform red colour, which confirms the good incorporation of dye molecules into the GEW. Spherical curvature of these microspheres is more evident in the SEM image (figure 2(b)). A high magnification SEM image of a single microsphere indicates a smooth surface (figure 2(c)), which is substantial for gaining a high optical confinement and low lasing threshold.

3.2. Lasing characteristics of a typical egg white based microsphere biolaser

The obtained dye-doped EW microspheres can work as efficient laser sources under optical excitation. Figure 3(a) plots the emission spectra of a single microsphere (about 43 μ m in diameter estimated from the microscope image) under increasing pump pulse energy (PPE). Each spectrum was excited by a single pulse. At a low PPE of 1.6 μ J, the emission is characterized by the spontaneous emission with low intensity and broad spectrum. Under higher PPE of 2.72 μ J, lasing modes start to appear with wavelengths from 610 to 620 nm and a clear free-spectral range (FSR) of around 1.84 nm is observed. The intensity of these lasing mode increases sharply with increasing PPE to 5.32 μ J. In addition, under this PPE, new lasing modes are now visible. These modes are suggested to have a different polarization compared with the original one (which will be discussed later). Figure 3(b) shows the integrated PL intensity from the microsphere as a function of PPE, indicating a distinct laser threshold of about 2.5 μ J. The threshold is equivalent to a fluence of 26 μ J mm⁻², which is comparable with dye-doped polymer microsphere lasers [12] and significantly lower than that of starch-based biolasers [13]. The lasing threshold depends on many factors including the dye concentration thus a lower lasing threshold can be obtained with an optimized dye concentration.

The lasing mechanism is ascribed to the whispering gallery mode (WGM) and the position of the lasing modes can be calculated by using the explicit asymptotic formula [26]. For a WGM laser, FSR = $\lambda^2/\pi nD$, where λ is the lasing wavelength, and *n* and *D* are the refractive index and diameter of the microsphere laser. As FSR and lasing wavelength can be measured from a lasing spectrum and $D = 43 \ \mu m$ thus the




Figure 1. Illustration of the fabrication process of dye-doped GEW microsphere.




Figure 2. Optical and SEM images of dye-doped GEW microspheres.

refractive index can be calculated to be around 1.491. Furthermore, lasing modes can be with transverse electric (TE) and transverse magnetic (TM) modes depending on the orientation of electric field oscillation [27]. As shown in figure 4(a), the spectrum displays two separated lasing envelope; the one with higher intensity is the TE modes (due to higher Q factor) while the one with lower intensity is the TM modes [28]. Assuming $D = 43 \ \mu m$ and n = 1.491, the TE and TM

modes are fitted well with a fundamental mode number of 312-319. To better confirm the WGM mechanism, TE lasing modes of microspheres with different sizes are compared with theoretical calculations and the result indicates an agreement between the experimental observation and WGM theory (figure 4(b)).

In addition, we have studied several lasers under long term pumping and the result indicates that the lasing operation




Figure 3. (a) Emission spectra from a single 43 μ m-diameter microsphere under various pump pulse energies. (b) Integrated PL intensity of the microsphere laser as a function of pump pulse energy. The scale bars are 50 μ m.




Figure 4. (a) Mode analysis of the lasing spectrum of the 43 μ m-diameter microsphere. (b) Agreement between theoretical calculation and experimental measurement of TE lasing modes of three different microspheres.

is quite stable. For instance, a 52 μ m-diameter microsphere continues lasing for as many as 3×10^3 excitation pulses. It is also worth noting that all the lasing properties were measured in air. Currently, our biolasers do not work in an aqueous environment. This issue has to be solved before applying these biolasers for biosensing applications.

3.3. Size-dependent lasing characteristics of egg white based microsphere biolasers

Size-dependence of lasing characteristics is investigated. Figure 5(a) plots the lasing spectra of three different

microspheres showing a red-shift of lasing wavelength with increasing microsphere diameter from 34 to 82 μ m. This effect has been observed and can be explained by the out-coupling efficiency in which a longer lasing wavelength is easier to scatter out of a microsphere with a larger size [29]. In addition to the red-shift of lasing wavelength, the FSR decreases with increasing the microsphere diameter. The change of FSR can be well explained by the expression FSR = $\lambda^2/\pi nD$, where λ is the lasing wavelength, and *n* and *D* are the refractive index and diameter of the microsphere. Based on that equation, it is expected that FSR would be a linear function with the inverse of microsphere diameter (1/*D*). This hypothesis is verified in




Figure 5. (a) Lasing spectra of microspheres with diameter of 34, 48 and 82 μ m (from low to high), respectively. (b) FSR of various microspheres as a function of their inverse diameter. (c) Q factor of microsphere lasers versus their diameter.

figure 5(b) where the FSR of 13 microspheres with diameters ranging from 34 to 160 μ m is plotted versus 1/D. The result confirms that WGM is responsible for the observation of lasing emission from dye-doped GEW microspheres.

The Q factor is an important parameter of a laser cavity that describes the optical confinement. A high Q factor cavity is desired for a low lasing threshold and ultrasensitive optical sensing [30]. As shown in figure 5(c), the Q factor (calculated as $Q = \lambda \delta \lambda$ of microsphere lasers increases from 2050 to 3100 with increasing microsphere diameter from 34 to 160 μ m. The obtained Q factor is comparable with that of protein based microsphere lasers [9, 24] and about three-times larger than that of the starch based lasers [13]. The Q factor increases gradually with increasing microsphere size because larger microspheres confine light better than smaller ones. The highest Q factor that can be detected is 3150 (at 630 nm) due to the spectral resolution (0.2 nm) of our setup. In addition, due to a lower Q factor, it is more difficult to observe lasing emission from small microspheres. The smallest lasing microsphere measured has a diameter of around 30 μ m.

4. Conclusion

We have demonstrated that EW is an excellent biomaterial for a laser cavity. By doping dye molecules into GEW and using a simple but effective method, dye-doped GEW microspheres with a diameter ranging from 20 to 160 μ m are fabricated. Under optical pulse excitation, these microspheres can work as efficient lasers with lasing threshold as low as 2.5 μ J or 26 μ J mm⁻² for a 43 μ m-diameter microsphere. The Q factor of these microsphere lasers is proportional to their diameter and can be reached to 3 × 10³ for a 160 μ m-diameter microsphere. The size-dependence of lasing characteristics is studied and the result shows a good agreement with the WGM theory. Our microsphere biolasers are very promising for biosensing and bioimaging applications.

Acknowledgments

This work was supported by Vietnam's Ministry of Science and Technology under Project ĐTĐLCN.24/18.

ORCID iDs

Hanh Hong Mai D https://orcid.org/0000-0002-5924-5112 Van Duong Ta D https://orcid.org/0000-0003-3961-714X

References

- [1] Chen Y-C and Fan X 2019 Adv. Opt. Mater. 7 1900377
- [2] Humar M and Hyun Yun S 2015 Nat. Photon. 9 572
- [3] Gather M C and Yun S H 2011 Nat. Photon. 5 406
- [4] Humar M, Dobravec A, Zhao X and Yun S H 2017 Optica 4 1080
- [5] Hansch T, Pernier M and Schawlow A 1971 EEE J. Quantum Electron. 7 45
- [6] Steckl A J 2007 Nat. Photon. 1 3
- [7] Oh H J, Gather M C, Song J-J and Yun S H 2014 Opt. Express 22 31411
- [8] Venkatakrishnarao D, Mohiddon M A and Chandrasekar R 2017 Adv. Opt. Mater. 5 1600613
- [9] Ta V D, Caixeiro S, Fernandes F M and Sapienza R 2017 Adv. Opt. Mater. 5 1601022
- [10] Caixeiro S, Gaio M, Marelli B, Omenetto F G and Sapienza R 2016 Adv. Opt. Mater. 4 998
- [11] Jaroslaw M, Konrad C, Lech S and Andrzej M 2017 J. Opt. 19 033003

- [12] Ta V D, Nguyen T V, Pham Q V and Nguyen T V 2019 Opt. Commun. 459 124925
- [13] Wei Y, Lin X, Wei C, Zhang W, Yan Y and Zhao Y S 2017 ACS Nano 11 597
- [14] Thakur R, Pristijono P, Scarlett C J, Bowyer M, Singh S P and Vuong Q V 2019 Int. J. Biol. Macromol. 132 1079
- [15] Ogunsona E, Ojogbo E and Mekonnen T 2018 Eur. Polym. J. 108 570
- [16] Stevens L 1991 Comp. Biochem. Physiol. B: Comp. Biochem. 100 1
- [17] Kovacs-Nolan J, Phillips M and Mine Y 2005 J. Agric. Food Chem. 53 8421
- [18] Abeyrathne E D N S, Lee H Y and Ahn D U 2013 Poult. Sci. 92 3292
- [19] Zhang W, Liu F, Nindo C and Tang J 2013 J. Food Eng. 118 62
- [20] Arakawa E T, Tuminello P S, Khare B N and Milham M E 2001 *Biopolymers* **62** 122

- [21] Capron I, Robert P, Colonna P, Brogly M and Planchot V 2007 Carbohydr. Polym. 68 249
- [22] Romanoff A L and Sullivan R A 1937 Ind. Eng. Chem. 29 117
- [23] Rickard D L, Duncan P B and Needham D 2010 *Biophys. J.* 98 1075
- [24] Nguyen T V, Pham N V, Mai H H, Duong D C, Le H H, Sapienza R and Ta V-D 2019 *Soft Matter*. **15** 9721
- [25] Liu Y, Huang Q, Wang J, Fu F, Ren J and Zhao Y 2017 Sci. Bull. 62 1283
- [26] Lam C C, Leung P T and Young K 1992 J. Opt. Soc. Am. B 9 1585
- [27] Humar M, Ravnik M, Pajk S and Musevic I 2009 Nat. Photon. 3 595
- [28] Ta V D, Chen R and Sun H D 2013 Sci. Rep. 3 1362
- [29] Tang S K Y, Derda R, Quan Q, Lončar M and Whitesides G M 2011 Opt. Express 19 2204
- [30] He L, Özdemir Ş K and Yang L 2012 Laser Photon. Rev. 7 1