#### PAPER

# Quantitative simulation of extracellular single unit recording from the surface of cortex

To cite this article: Mackenna Hill et al 2018 J. Neural Eng. 15 056007

#### Manuscript version: Accepted Manuscript

Accepted Manuscript is "the version of the article accepted for publication including all changes made as a result of the peer review process, and which may also include the addition to the article by IOP Publishing of a header, an article ID, a cover sheet and/or an 'Accepted Manuscript' watermark, but excluding any other editing, typesetting or other changes made by IOP Publishing and/or its licensors"

This Accepted Manuscript is©.

#### $\odot$

During the embargo period (the 12 month period from the publication of the Version of Record of this article), the Accepted Manuscript is fully protected by copyright and cannot be reused or reposted elsewhere.

As the Version of Record of this article is going to be / has been published on a subscription basis, this Accepted Manuscript will be available for reuse under a CC BY-NC-ND 3.0 licence after the 12 month embargo period.

After the embargo period, everyone is permitted to use copy and redistribute this article for non-commercial purposes only, provided that they adhere to all the terms of the licence <u>https://creativecommons.org/licences/by-nc-nd/3.0</u>

Although reasonable endeavours have been taken to obtain all necessary permissions from third parties to include their copyrighted content within this article, their full citation and copyright line may not be present in this Accepted Manuscript version. Before using any content from this article, please refer to the Version of Record on IOPscience once published for full citation and copyright details, as permissions may be required. All third party content is fully copyright protected, unless specifically stated otherwise in the figure caption in the Version of Record.

View the article online for updates and enhancements.

# Quantitative simulation of extracellular single unit recording from the surface of cortex

Mackenna Hill<sup>1,2⊥</sup>, Estefania Rios<sup>1⊥</sup>, Shyam Kumar Sudhakar<sup>3</sup>, Douglas H. Roossien<sup>4</sup>, Ciara Caldwell<sup>1</sup>, Dawen Cai<sup>4,5,6</sup>, Omar J. Ahmed<sup>1,3,5</sup>, Scott F. Lempka<sup>1,7</sup>, Cynthia A. Chestek<sup>1,8</sup>

<sup>1</sup>Department of Biomedical Engineering, University of Michigan, Ann Arbor, MI, USA

<sup>2</sup>Department of Biomedical Engineering, Duke University, Durham, NC, USA <sup>3</sup>Department of Psychology, University of Michigan, Ann Arbor, Michigan, USA <sup>4</sup>Department of Cell and Developmental Biology, University of Michigan, Ann Arbor, Michigan, USA

<sup>5</sup>Neuroscience Graduate Program of the Medical School, University of Michigan, Ann Arbor, Michigan, USA

<sup>6</sup>Department of Biophysics of LS&A, University of Michigan, Ann Arbor, Michigan, USA

<sup>7</sup>Biointerfaces Institute, University of Michigan, Ann Arbor, MI, USA

<sup>8</sup>Electrical Engineering, Neuroscience, and Robotics, University of Michigan, Ann Arbor, MI, USA

 $^{\perp}$ M. Hill and E. Rios contributed equally.

E-mail: cchesteck@umich.edu

Abstract. Objective. Neural recording is important for a wide variety of clinical applications. Until recently, recording from the surface of the brain, even when using micro-electrocorticography ( $\mu ECoG$ ) arrays, was not thought to enable recording from individual neurons. Recent results suggest that when the surface electrode contact size is sufficiently small, it may be possible to record single neurons from the brain's surface. In this study, we use computational techniques to investigate the ability of surface electrodes to record the activity of single neurons. Approach. The computational model included the rat head,  $\mu ECoG$  electrode, two existing multi-compartmental neuron models, and a novel multi-compartmental neuron model derived from patch clamp experiments in layer 1 of the cortex. Main Results. Using these models, we reproduced single neuron recordings from  $\mu$ ECoG arrays, and elucidated their possible source. The model resembles the experimental data when spikes originate from layer 1 neurons that are less than  $60 \ \mu m$  from the cortical surface. We further used the model to explore the design space for surface electrodes. Although this model does not include biological or thermal noise, the results indicate the electrode contact area should be 100  $\mu$ m<sup>2</sup> or smaller to maintain a detectable waveform amplitude. Furthermore, the model shows the width of lateral insulation could be reduced, which may reduce scar formation, while retaining 95% of signal amplitude. Significance. Overall, the model suggests single-unit surface recording is limited to neurons in layer 1 and further improvement in electrode design is needed.

*Keywords*: micro-ECoG, electrocorticography, Neural recording, Brain-computer interfaces, Computational model, Computer simulation, Microelectrodes

55

56

57

58

59

Quantitative simulation of extracellular single unit recording from the surface of cortex

#### 1. Introduction

Neurological diseases can significantly decrease the quality and duration of life. Neural recording electrodes are utilized as diagnostic tools and in therapeutic devices for a wide variety of conditions. Macroelectrode recording applications, such as invasive monitoring for epilepsy [1, 2] and local field potential recordings obtained from electrodes used in deep brain stimulation [3], use large surface area electrodes ( $\sim$ 30 mm<sup>2</sup> to  $\sim$ 0.3 mm<sup>2</sup>) to record the activity of a large number of neurons within the brain. Microelectrode recording applications use small surface area electrodes ( $\sim$ 1000  $\mu$ m<sup>2</sup> to  $\sim$ 10  $\mu$ m<sup>2</sup>) that can record the activity of single neurons. Microelectrodes are required for high resolution brain-machine interfaces (BMI) which are devices that aim to restore motor, sensory, and/or cognitive function [4, 5, 6].

Penetrating electrodes arrays have been used for decades in BMI applications. Common devices include the Utah array and the Michigan probe [7, 8, 9]. These types of electrodes have high spatial resolution and can record the activity of individual neurons (single units). However, all penetrating electrodes have limitations which prevent their widespread use, such as damage to the blood brain barrier, scarring from the foreign body reaction, and the inability to record from neurons greater than ~100  $\mu$ m from the electrode surface [10, 11, 12, 13, 14]. Recent advances in cellular-scale electrodes have mitigated some of these concerns [15, 16], but these novel arrays have lower channel counts and are not yet ready for clinical use.

Surface electrodes can address many of the limitations of penetrating electrodes. These electrodes are applied to the surface of the brain rather than being inserted into the brain. Thus, these surface electrodes do not disrupt the blood brain barrier. As a result, surface electrocorticography (ECoG) electrodes avoid brain damage and

Quantitative simulation of extracellular single unit recording from the surface of cortex potentially increase long-term viability. However, ECoG electrodes have their own limitations. Because they present an impermeable solid surface to the brain, this may cause increased scarring over time [10, 17, 18, 19]. The primary limitation of ECoG electrodes is an increased distance between the electrodes and the neurons of interest. This distance decreases the selectivity of conventional ECoG electrodes so that they are only able to record ensemble activity [1, 20]. The inability to selectively record from small populations of neurons is logical because neural signals quickly fall off as function of distance from the electrode [21, 11].

Recently, one novel micro-electrocorticography ( $\mu ECoG$ ) grid was reported to overcome some of these limitations. Khodagholy et al. 2015 [22] designed a  $\mu ECoG$ grid (NeuroGrid), with much smaller electrode sizes than previous devices (100  $\mu$ m<sup>2</sup>), that was able to record signals at the brain surface that appear to be generated by single units in rats. Due to the clear advantages of surface recording, it is important to understand which type of neurons are being recorded, how deep these recordings extend, and the critical aspects of the electrode design that provide these unique capabilities.

The purpose of this study was to investigate these issues and the origin of the neural signals recorded with these  $\mu ECoG$  surface microelectrodes using a computational modeling approach. Therefore, we built a computational model of surface recording, adapting the methods of Moffitt and McIntyre 2005 [11]. To our knowledge, this is the first neural recording model capable of replicating singleunit recording from the surface of the brain. First, we used two existing multicompartmental cable models of pyramidal cells from layers 3 and 5 [23, 24] and developed a novel multi-compartment model that matched patch clamp data from layer 1 cells. Next, we developed finite element models (FEM) of electrodes with the NeuroGrid geometry along with several variants. Finally, we used a reciprocal solution approach to estimate the extracellular voltages that would be observed with

Quantitative simulation of extracellular single unit recording from the surface of cortex 4 recording electrodes of various sizes. We believe this model will help to determine the origin of single-unit recordings from  $\mu$ ECoG electrode grids as well as potential technological improvements that can be made to optimize the recording fidelity.

#### 2. Methods

#### 2.1. Neuron Models

In this study, we performed simulations for several different neuron models. We designed a novel closed-field layer 1 neurogliaform interneuron model that was parameterized to match patch clamp data, as described in detail below. We also implemented open-field layer 3 and layer 5 pyramidal neuron models [23, 24]. In the final analysis, we simplified the layer 5 pyramidal neuron so it could be scaled to different sizes. These models helped determine the absolute maximum recording depth for common types of neurons in varying layers of the brain and acted as possible sources for the single-unit signals reported in Khodagholy et al. 2015 [22]. The geometries of all cell models are shown in Figure 1.

To consider signals from layer 1 neurons, we built a computational model of a layer 1 neurogliaform neuron of the neocortex based on published layer 1 patch clamp currents [25]. A previous study obtained the morphology of the neuron [26], available at neuromorpho.org. We imported the morphology into the HOC format of the software package, NEURON, using the built-in import3D tool [27]. The model had an active somatic compartment and 45 passive dendritic compartments. We calculated the number of segments in each compartment (nseg) using the dlambda rule [27]. We then tuned the model parameters to obtain biologically realistic properties. This tuning was done in two stages: We first turned the model's passive properties. We tuned the model's specific membrane resistance  $(15.4 \text{ k}\Omega \text{ cm}^2)$  to match the time constants (15.4 ms) and input resistance (297MΩ)

Quantitative simulation of extracellular single unit recording from the surface of cortex with experimental values [25]. Next, we tuned the model's active properties to match the spike shape characteristics with that of the experimental data. For this purpose, we inserted Hodgkin-Huxley type [28] voltage-gated sodium and delayed rectifier potassium currents into the model's somatic compartment. The currents are based on a previously-published study that included neurogliaform cells [29] (see Appendix A for equations). We tuned the maximal channel conductance (gmax) values of voltage-gated sodium and potassium channels using a brute force search approach and feature based error functions [30, 31]. We then chose the features: spike width, spike threshold, spike amplitude and after-hyperpolarization amplitude. By assuming parameter specific maximum values, we evaluated the error function at equidistant points in the parameter space [30]. The resulting model (Na gmax  $= 2 \text{ S/cm}^2$ , K gmax  $= 0.3 \text{ S/cm}^2$ ) had a spike threshold of -49.4 mV and a spike width of 0.805 ms closely replicating the spike shape of experimentally-measured neurogliaform neurons. The model's spike amplitude was 44% larger than that of experimental data [25]. We performed all simulations at 32 °C. To model the temperature dependence of the ionic currents, we employed a q10 value of 3 to scale the gating time constants of channel currents. The model had a resting membrane potential of -82.36 mV.

We also included well-established models of layers 3 and layer 5 open-field pyramidal cells [23, 24]. We only considered open-field pyramidal neurons because their long and thick apical dendrites can lead to significant spatial separation between sources or sinks and the corresponding return currents that produce significant ionic currents in the extracellular space [32]. We reasoned these open-field neurons would produce spikes that would be most likely to appear in extracellular recordings from electrodes at distant locations.

Finally, we created a simplified version of the layer 5 pyramidal neuron from Mainen et al. 1995 [23] to scale the neuron size with all other parameters held

Quantitative simulation of extracellular single unit recording from the surface of cortex constant [23, 33]. This allowed us to explore potential difficulties when recording from small neurons with most surface and penetrating electrodes. We kept the channel types, channel dynamics, and overall ion channel counts within each part of the cell consistent with the Mainen model. However, we simplified the overall neuron geometry. The axon was shortened to a single myelinated 200-compartment section with a length of 100  $\mu$ m and a diameter of 1  $\mu$ m since the axon makes a small contribution to the extracellular action potential [34, 35]. The axon hillock compartments were kept the same with the diameters increasing from 1 to 9  $\mu$ m approaching the soma. For the soma, the cylindrical compartment was set to a diameter of 24  $\mu$ m and height of 21  $\mu$ m to match the neuron size used in the original layer 5 model [23, 36]. Finally, we consolidated the elaborate dendritic arbor in Mainen et al. 1995 [23] into a single thick dendrite with 222 segments, length of 1030  $\mu$ m, and a diameter of 12  $\mu$ m. While the length of the apical dendrite compartment remained approximately the same, we increased the diameter so that the total surface area matched that of the original dendritic arbor (65,000  $\mu$ m<sup>2</sup>) [37, 34]. In all regions of the cell, we calculated the channel density such that the overall density of ion channels in each section of the neuron remained the same as the original model from Mainen et al. 1995 [23]. When altering the neuron size, we linearly scaled the entire model geometry to match the soma diameter of the neuron in question.

We performed all simulations within the NEURON 7.2 simulation environment. To generate action potentials in the layer 1, 3, and 5 pyramidal cell models, we injected current into the soma. To generate action potentials in the simplified pyramidal cell model, we injected a brief pulse of current into the axon hillock at the minimum current which would cause an action potential (pulse width = 7 ms, pulse amplitude = 0.7 nA for a 24  $\mu$ m diameter neuron). For each neuron model, we solved the time-dependent transmembrane currents in each compartment.

 2.2. Volume Conductor Model

To evaluate the effects of electrode size, position, and insulation, we created finite element models (FEM) of a rat brain and  $\mu$ ECoG electrodes. Similarly to Moffitt and McIntyre, 2005 [11] this model included rodent head dimensions with representations of the brain, cerebrospinal fluid (CSF), skull, and scalp as shown in Table 1. We implemented an electrostatic model with the above dimensions in COMSOL 5.2a (Comsol Inc., Burlington Massachusetts). When the mesh spacing was reduced 2 fold, the mean squared error between the two solutions was 0.0107  $\mu$ V. Thus, the mesh was determined stable. For computational simplicity, we flattened the top of the brain, forming a circle with a diameter of 1130  $\mu$ m. Although  $\mu$ ECoG electrodes traditionally sit on top of the pia, we assumed the pia to have a conductivity equal to the brain since the pia exerts a negligible difference on field potential distribution [38, 39, 40].

The microelectrodes within this model were based on the electrodes described in Khodagholy et al. 2011 [41] and Khodagholy et al. 2015 [22]. The electrode consisted of a 10 x 10 x 8  $\mu$ m<sup>3</sup> volume of gold surrounded by a 10 x 10 x 10  $\mu$ m<sup>3</sup> cube of PEDOT:PSS backed by a 2  $\mu$ m thick layer of parylene-c insulation extending for 50  $\mu$ m past the electrode on either side, meant to simulate full insulation coverage (Figure 3). For comparison a single, more accurate, representation of the electrode was created with 10 x 10 x 1.79  $\mu$ m<sup>3</sup> of a PEDOT:PSS/Ethylene Glycol mix on top of a 10 x 10 x 0.21  $\mu$ m<sup>3</sup> solid gold electrode backed by a 150 x 150 x 2  $\mu$ m<sup>3</sup> parylene-c substrate with parylene-c, 2  $\mu$ m thick, surrounding the electrode laterally. A difference of less than 1% was observed between the two models. The electrode contact was placed at the top of the brain with the skull acting as the ground. The electrical conductivities for each material are listed in Table 1. We also created variants of this electrode with different contact sizes and width of lateral insulation.

Quantitative simulation of extracellular single unit recording from the surface of cortex

To achieve a model solution, we applied the necessary load and boundary conditions. The load condition consisted of a unit current source (i.e. 1 A) placed at the recording electrode [11, 39, 42]. The boundary conditions required that the voltage attenuated to zero at the skull. The electrostatic model was solved in COMSOL using a linear solver.

#### 2.3. Waveform Calculation

To estimate the neural spike waveforms recorded from a particular electrode and neuron, we used a reciprocal solution [11, 42] to couple the volume conductor FEM to the neuron models. Each compartment of a neuron model was represented as an independent current source (i.e. the time-dependent transmembrane currents computed in NEURON) at the appropriate spatial location in the FEM. We then calculated the recorded waveform by summing the voltages generated at the electrode contact by each of the transmembrane currents of the individual neuron compartments. Briefly, the reciprocal solution involved placing a unit current source at the recording electrode and solving for the scalar potentials generated at each node in the FEM. By the theorem of reciprocity, the voltage at a given node in the mesh could be interpreted as the voltage generated at the recording electrode for a unit current. Therefore, we calculated the contribution of each neural compartment to the recorded waveform using interpolation of the voltages from the nearest nodes surrounding each neural compartment. See Moffitt and McIntyre, 2005 [11] and Lempka et al., 2011 [42] for additional details describing this reciprocal solution approach.

## 2.4. Cortical Layer Imaging

We performed immunohistochemistry to estimate the average diameter, surface area, and density of neural somata in layer 1 of mammalian cortex as well as the thickness

Quantitative simulation of extracellular single unit recording from the surface of cortex of layer 1. We performed all animal procedures in accordance with the institutional animal guidelines and approval of the University of Michigan IACUC. For histology, we perfused WT Long-Evans wild-type rats under anesthesia first with cold saline followed by 10% Neural Buffer Formalin (NBF, Millipore). We removed brains which were postfixed for 16 hours in fresh 10% NBF with gentle shaking at 4°C. Next, we mounted sections in 2% agarose gel (ThermoFisher) in homemade 1X Phosphate Buffer Saline (PBS) and cut at 100  $\mu$ m thickness using a Leica VT1000S vibratome. Then, we blocked sections in StartingBlock-PBS (ThermoFisher) with 1.0% Triton X-100 overnight at 4°C with gentle shaking. We incubated section in mouse antineuronal nuclei (NeuN) primary antibody (1:250, Millipore) in PBS containing 0.5% Triton X-100 for 3 days at  $4^{\circ}$ C with gentle shaking [43]. We then incubated sections for 2 days in donkey anti-mouse Alexa Fluor 647 (1:500, Jackson ImmunoResearch) and NeuroTrace 435/455 (1:250, Life Technologies) in PBS with 0.5% TritonX-100. We washed sections three times between each incubation using PBS with 0.5% Triton X-100 for one hour each at room temperature. We mounted sections in Vectashield mounting medium (Vector Labs). Finally, we imaged sections at 1  $\mu$ m intervals in the z-dimension on a Zeiss LSM 780 using 405nm and 633nm lasers for excitation together with -405 and 488/543/633 dichroic mirrors.

#### 2.5. Density and Morphology of Neurons in Upper Layers

From the histology images described in Section 2.4, we observed  $718 \pm 30.4$  neurons per plane with an average radius of  $4.59 \pm 1.40 \,\mu m$  (n=53,106) over all cortical layers. Due to the small plane thickness, we counted individual neurons multiple times. We then modeled the neurons as spheres and the center of each neuron was determined using Fiji/ImageJ v1.48 [44, 45]. If the center was within 2  $\mu$ m on subsequent planes, we considered the neurons to be one neuron captured by multiple planes. Once we removed these duplicated neurons there were a total of 17,901 neurons with an

Quantitative simulation of extracellular single unit recording from the surface of cortex average radius of  $4.98 \pm 1.60 \ \mu m$  and  $344 \pm 220 \ \mu m^2$  surface area over all cortical layers. As seen in Figure 4 we separated the layers of cortex and calculated the neuron density, neuron radius, and layer thickness. Average neuron size informed the size of our neuron model for layer 1 neurons. We identified each layer by the neuron density and morphology with pia containing no neurons and having a lighter appearance, layer 1 containing sparse neurons, layer 2/3 increasing drastically in density, layer 4 neurons increasing in soma size, and layer 5 neurons decreasing in soma size. These distinctions, as well as a single optical section of brain, can be seen in Figure 4. The depth of the pia  $(20.2 \pm 1.58 \ \mu m)$  set a minimum distance between the electrode and a neuron since neurons do not typically exist in the pia. Since the pia was removed from the rat brain during processing, mouse slices stained with NeuN were used from another study. The depth of the other layers indicated at what depth a large change in neuron density would occur as well as the type of neuron that may be recorded at specific recording depths.

#### 3. Results

#### 3.1. Replication of Experimental Recordings

First, we used our model to simulate spikes that could potentially be recorded from multiple layers of the brain using an electrode resembling the  $\mu$ ECoG arrays used in Khodagholy et al. 2015 [22]. This electrode was 10 x 10  $\mu$ m<sup>2</sup>, with 110 x 110  $\mu$ m<sup>2</sup> of parylene immediately adjacent to the pia with no CSF between the electrode and the pia, as shown in Figure 3. These parameters represent a favorable recording environment, assuming perfect electrode adhesion to tissue. Using the models described above for layer 1, layer 3, and layer 5 neurons, we simulated the resulting spike waveforms on the electrodes and measured the peak-to-peak amplitudes. Recorded waveforms for the cells in each layer are shown across the top

Quantitative simulation of extracellular single unit recording from the surface of cortex of Figure 5.

The only simulation that produced a detectable spike (> 48  $\mu$ V<sub>pp</sub>) was a layer 1 cell placed at the very top of pia, 20  $\mu$ m away from the recording electrode. If we assume a minimum signal-to-noise ratio (SNR) of 2 to reliably detect a spike and a 12- $\mu$ V recording noise for a 100  $\mu$ m<sup>2</sup> electrode [42], then the smallest detectable neuronal spike is ~48  $\mu$ V (i.e.  $V_{min} = SNR * 2 * \sigma_{noise}$ ). While the layer 1 neuron spike was very large at 20  $\mu$ m (400  $\mu$ V, larger than seen in Khodagholy et al. 2015), it dropped to 50  $\mu$ V at only 60  $\mu$ m away from the electrode. The large V<sub>pp</sub> at an electrode-to-neuron distance of 20  $\mu$ m may be attributable to perfect soma positioning and lack of any CSF at the electrode site (modeled below). Models of neurons from layers 3 and 5 only produced very small spikes at the brain surface with rising edge first. In all cases, the amplitude was below 1  $\mu$ V. Therefore, we focused on layer 1 neurons for the remaining analyses in this study.

Layer 1 cell recording could also reproduce how neurons in Khodagholy et al. 2015 [22] appear on a single contact or adjacent contacts with detectable amplitudes, but rarely on any distant contacts. Figure 6 shows the waveform amplitude from a simulated layer 1 neuron 20  $\mu$ m away. It had a peak-to-peak amplitude of 400  $\mu$ V on the closest contact, a detectable amplitude of 60  $\mu$ V on the adjacent contact, with 30  $\mu$ m between the 10 x 10  $\mu$ m<sup>2</sup> electrodes, and an amplitude of 4.5  $\mu$ V two contacts away. The model shows that a neuron placed 30  $\mu$ m deep, directly between two contacts, produces an amplitude of 135  $\mu$ V on each contact. If we assume a maximum recording depth of 60  $\mu$ m, we would be able to record activity from ~20 neurons under a 160 x 320  $\mu$ m electrode grid (NeuroGrid) based on the layer 1 thickness and neuron density (9830 neurons mm<sup>-3</sup>) estimated from our histology results.

Our computational model posited the ideal scenario for recording in which the largest factors affecting the accuracy of this estimate were electrode adhesion to the Quantitative simulation of extracellular single unit recording from the surface of cortex 12 brain and neuron size. With the addition of a few microns of CSF between the electrode and the brain, the signal decreased by approximately 50%. With CSF present, the estimate of the number of recordable neurons decreased from 20 to 4 neurons. These estimates included 20  $\mu$ m of pia between the electrode and layer 1 yet other studies indicate that pia is slightly thicker in rats (~25  $\mu$ m; [46]). If the thickness of pia in rats was increased to 30  $\mu$ m, then the estimate of the number of recordable neurons. The theoretical estimate agreed well with experimental data in which the activity of ~9 individual neurons was consistently detected with the NeuroGrid [22].

#### 3.2. Effects of Electrode Geometry, Insulation, and Adhesion

After Validating the model against experimental results, we explored the design space of electrodes capable of recording surface single units in terms of size, insulation, and adhesion. Electrode surface area is a critical design parameter, with site sizes of 100  $\mu$ m<sup>2</sup> or smaller requiring highly conductive surface preparations and microfabrication due to their high impedance [47, 22]. Figure 7(a) shows the recording amplitude as a function of electrode surface area for a layer 1 neuron 20  $\mu$ m from the electrode. The recording amplitude rapidly decreases for electrode surface areas larger than 100  $\mu$ m<sup>2</sup>, which suggests electrodes should have surface areas  $\leq 100 \ \mu$ m<sup>2</sup> to detect single-unit activity from the brain surface. Therefore, previous  $\mu$ ECoG electrodes may not have been small enough to detect single units.

Insulation was also critical for high recording amplitudes in the model. Electrodes without insulation (i.e. parylene replaced with CSF) produced low recording amplitudes (Figure 7(a)). Therefore, we also varied the amount of insulation on the back of the electrodes as shown in Figure 7(b). To maintain 95% of the signal amplitude, 60 x 60  $\mu$ m<sup>2</sup> lateral insulation was required for a 10 x 10  $\mu$ m<sup>2</sup> recording electrode surface area.

Quantitative simulation of extracellular single unit recording from the surface of cortex

Blood flow and respiration can cause micromovements of the brain where the brain may move vertically up to 4  $\mu$ m and 30  $\mu$ m, respectively [48]. To model the effect of these micromovements, as well as electrode adhesion in general, we added a layer of CSF between the insulation and the brain as shown in Figure 7(c). We tested CSF thicknesses of 3.5  $\mu$ m and 30  $\mu$ m that reduced the recording amplitude by 55% and 97%, respectively. This result suggests that that adhesion is also critical for high amplitude recording.

#### 3.3. Effects of Neuron Size and Channel Density

The results above suggest that there can be non-obvious interactions between cell size, distance, and that electrode design choices may significantly impact recording sensitivity. While the distance relationship is well understood [11], we sought to model the effect of neuron size, independent of other parameters. As described in section 2.1, we created a simplified neuron model based on the well-established layer 5 model [23, 24]. Our simplified model used a line of cylinders with equivalent ion channel densities. When we scaled the reduced model to have a soma diameter equal to the diameters of the more detailed models (18  $\mu$ m for layer 3, 24  $\mu$ m for layer 5), the spike amplitudes of the reduced model were within 13.3 and 1.0 percent of the spike amplitudes of the layer 3 and layer 5 cell models, respectively (Figure 8(a-b)). Figure 8(c) shows the effect of scaling the neuron size on voltage amplitude. Overall, if channel densities and properties remain constant as the size of the neuron increases, waveform amplitude scales with some diameter squared, or equivalently the waveform amplitude scales linearly with some surface area. This trend is observed because the number of ion channels, and thus the transmembrane current, are scaling with the area in our simplified model and the voltage is linearly proportional to the transmembrane current. In this model, a neuron with a 10  $\mu$ m diameter would produce a peak-to-peak spike amplitude of 66.8  $\mu V$  (compared to Quantitative simulation of extracellular single unit recording from the surface of cortex 14 307  $\mu$ V for the 24  $\mu$ m layer 5 cell), an 8  $\mu$ m diameter neuron would produce a spike amplitude of 46.0  $\mu$ V (our estimated minimum detectable signal), and a 5  $\mu$ m diameter neuron would produce a spike amplitude of 18.5  $\mu$ V. We altered the density of Na<sup>+</sup> and K<sup>+</sup> ion channels in the simplified neuron by  $\pm$  50% to determine if these results are sensitive to the specific channel density chosen. The largest signal increase was 7.8% and occurred when the Na<sup>+</sup> channel density was increased and the K<sup>+</sup> channel density was decreased. The largest signal decrease was -1.8% and occurred when the Na<sup>+</sup> channel density was decreased and the K<sup>+</sup> channel density was increased.

#### 4. Discussion

In this modeling study, we explored possible sources of single-unit recordings from  $\mu$ ECoG electrodes and examined how future electrode designs can take advantage of this remarkable capability. Towards this end, we used 3 neuron models: a layer 1 neurogliaform cell, a layer 5 pyramidal cell, and a layer 3 pyramidal cell [23, 24]. We also created a novel neuron model, based on a simplification of a layer 5 pyramidal cell, which could be scaled to illustrate the relationship between neuron size and  $V_{pp}$  [23, 24]. We then developed a volume conductor model of the rat head along with various  $\mu$ ECoG electrode designs to determine the effect of electrode size and insulation geometry on  $V_{pp}$  [11, 49, 39]. The results of our model analyses agreed well with experimental recordings from the literature [22] and predicted the effects of electrode design (e.g. the effect of electrode contact size and insulation geometry) on extracellular recording amplitude.

Specifically, a naive application of a 10 x 10  $\mu$ m<sup>2</sup> electrode and a layer 1 neurogliaform cell appeared to accurately replicate the experimental results in Khodagholy et al. 2015 [22]. Although we recorded a signal from layer 3 and 5

Quantitative simulation of extracellular single unit recording from the surface of cortex 15 pyramidal neurons in a noise-free environment, the  $V_{pp}$  were less than 1  $\mu$ V. While dendritic currents in aggregate may contribute to low-frequency local field potentials [50, 51], this model suggests dendrites originating from a single neuron are not the source of observed spikes on the surface of the cortex. Furthermore, the density of neuron cell bodies in layer 1 match the density of recorded spikes in Khodagholy et al. 2015 [22], indicating that the single-unit recordings in Khodagholy et al. 2015 likely originate from layer 1 neurons.

In this study, we developed a scalable neuron model that allowed us to examine how  $V_{pp}$  scaled with neuron size. Our results suggest  $V_{pp}$  decayed rapidly with decreasing cell size and cells smaller than 8  $\mu$ m would be difficult to detect with recording electrodes even at very close distances (Figure 8). The difficulty of recording from neurons smaller than 8  $\mu$ m in diameter is consistent with experimental data showing the challenges of recording from areas with predominantly small neurons, such as songbird areas and dorsal striatum [52, 53]. This result further highlights that single-unit recordings, particularly those from electrodes with large recording surfaces, have been biased toward recording signals from large neurons.

Using the base electrode model developed in this study, we made changes to the surface area of the electrode and the size of the lateral insulation. We determined that increasing the size of the electrode decreased the recording amplitude. The decrease in measured voltage when increasing the surface area of the electrode is expected due to spatial averaging of the voltage over a larger surface area [54, 21, 11, 55]. Furthermore, our model showed a rapid decrease in recording amplitude for electrodes larger than 100  $\mu$ m<sup>2</sup> (Figure 7(a)), indicating that an electrode surface area  $\leq 100 \ \mu$ m<sup>2</sup> may be an ideal size for  $\mu$ ECoG arrays. The amount of lateral insulation also significantly affected the recording amplitude. For electrodes with no lateral insulation, recording amplitudes were small and would

Quantitative simulation of extracellular single unit recording from the surface of cortex 16 likely be undetectable (Figure 7(a)). However, with 3600  $\mu$ m<sup>2</sup> of lateral insulation, the recording amplitude was 95% of the signal amplitude for a 10x10  $\mu$ m<sup>2</sup> electrode contact with an effectively infinite amount of lateral insulation.  $\mu$ ECoG arrays with this amount of lateral insulation have been fabricated previously [41, 56]. Since the changes to the model are independent, the effects of electrode geometry, insulation, and adhesion, as well as the effects of neuron size and channel density, can be combined using superposition. These results suggest that although  $\mu$ ECoG electrode contact dimensions should shrink to the cellular level, the insulation needs to remain fairly large in comparison.

In our model analysis, we also considered the effects of micromovements related to blood flow and respiration that could occur due to non-ideal adhesion between the brain and the electrode. We represented these micromovements using an additional layer of CSF with a variable thickness. This CSF layer substantially decreased the recording amplitude (i.e. 55% and 97% for CSF layers of 3.5  $\mu$ m and 30  $\mu$ m, respectively). This is due to the decreased resistance between the electrode and the neurons as well as the low resistance pathway to ground that the CSF provides [11]. This result suggests that adhesion is critical for high-amplitude recordings. Although the adhesion of  $\mu$ ECoG electrode arrays to the brain has not been fully investigated, it has been shown that electrode arrays thinner than 5  $\mu$ m conform well [22, 56]. Further, adhesion and flexibility of  $\mu$ ECoG electrode arrays continue to increase through the addition of holes to the substrate and a decrease in array thickness [56].

It is important to note that neurons needed to be within 60  $\mu$ m of the recording contact to obtain a signal over 50  $\mu$ V. This short distance raises the question of whether or not these electrodes could function under chronic recording conditions in which they would be surrounded by encapsulation tissue. Previous modeling studies have shown that an increase in tissue resistance due to electrode encapsulation may

Quantitative simulation of extracellular single unit recording from the surface of cortex actually increase the recording amplitude [11, 57]. However, experimental results suggest that ECoG electrodes can develop thick scars ( $\sim 1-2 \text{ mm}$ ) [19] that would likely increase the distance between the electrode and the neurons and produce a corresponding decrease in the recording amplitude. It could be possible to use electrode arrays with elements less than 15  $\mu$ m in diameter to mitigate scarring [58]. At 10 x 10  $\mu$ m<sup>2</sup> the electrode would be small enough to reduce scar formation, but the necessary insulation (> 3600  $\mu$ m<sup>2</sup>) would cause scarring when chronically implanted. Thus, biocompatible coatings may be needed for chronically viable electrodes (e.g. Azemi et al. 2008 [12] and Jorfi et al. 2015 [14]).

Although this study provided a means to systematically analyze the origin of single-unit surface recordings with  $\mu ECoG$  electrodes and the effects of electrode design, our model infrastructure was subject to a number of limitations. First, we made the standard assumption that the electrical properties of the biological media were resistive and linear within the context of neural recording [59]. Model solutions were static and did not consider the resistive and capacitive properties of the electrode-electrolyte interface of the recording electrodes. However, for welldesigned recording systems, the electrode-electrolyte interface has a minimal effect on the recorded signal [55, 60, 61, 62]. Second, the rat brain anatomy was simplified and represented by four concentric spheres. However, previous work has shown that computer models of extracellular microelectrode recordings are largely insensitive to the geometry of the head model [11, 39]. Third, because we only considered acute neural recordings in this study, we did not investigate the effects of electrode encapsulation and the corresponding changes in tissue impedance surrounding the electrode that could potentially affect the recording amplitude for a given electrode design [11, 57]. Fourth, in the simplified layer 5 pyramidal neuron model, we collapsed the dendritic arbor into one large apical dendrite which increases the length constant of the neuron. This increase in length constant could make the

Quantitative simulation of extracellular single unit recording from the surface of cortex 18 neuron electronically compact and produce a small increase in the amplitude of the extracellular action potential [37, 34]. Fifth, although the simulated layer 1 neuron came from a validated study, it is larger than the average layer 1 neuron. When the neuron model spike size was matched artificially, the spike size decreased by 56%. Finally, we did not incorporate noise sources (e.g. thermal, biological) into our model analysis. Recording noise sources, such as thermal noise, could play a significant role in determining the optimal contact size since these noise sources can vary with contact size [63, 42].

#### 5. Conclusion

In this study, we used a computational model of neural recording with  $\mu ECoG$ electrodes to investigate the ability to record individual neurons from the surface of the brain and determine the design parameters that support single-unit recording. Our modeling results corroborated experimental data demonstrating single-unit recordings with  $\mu ECoG$  electrodes. Our results also suggested that these signals most likely originate from layer 1 of cortex [22]. It is important to note that the recording amplitude, and consequently the recording depth, depend heavily upon the adhesion of the electrode to the brain. Although  $\mu ECoG$  electrodes cannot record from deep layer neurons, many applications that consistently utilize interneurons in superficial layers of the brain, such as epilepsy, would benefit from recording that activity of superficial neural signals [1, 20]. In this study, we also characterized the recording amplitude's dependence on lateral insulation and electrode size. Model results show that both design parameters significantly affected the recording amplitude and these parameters must be considered in future studies. In spite of the challenges, the ability to record individual neurons without penetrating the brain provides new scientific and clinical opportunities that may change how we interact with the brain.

## Acknowledgments

The authors would like to thank Jonathan Viventi Ph.D. for insightful comments on this paper. This work was supported by multiple grants from the National Institute of Health: 5R01 MH110932, 3U01 NS094375, and NIH BRAIN Initiative grants 5U01 NS094375-02 and 1R03 MH111316-01. The work was also supported by the National Science Foundation's International Program for the Advancement of Neurotechnology (IPAN), the American Epilepsy Society Junior Investigator Award, and a miBRAIN grant.

Quantitative simulation of extracellular single unit recording from the surface of cortex

# Appendix A. Equations for layer 1 neuron ion channel currents

Fast sodium current

$$\alpha_m = -0.034133 \times \frac{\nu + 24}{exp(\frac{\nu + 24}{-5}) - 1} \tag{A.1}$$

$$\beta_m = 0.2848 \times \frac{\nu - 4}{exp(\frac{\nu - 4}{5}) - 1} \tag{A.2}$$

$$\tau_m = \frac{1}{\alpha_m + \beta_m} \tag{A.3}$$

$$m_{\infty} = \frac{\alpha_m}{\alpha_m + \beta_m} \tag{A.4}$$

$$\alpha_h = \frac{0.29648}{exp(\frac{\nu+64.4184}{20})} \tag{A.5}$$

$$\beta_h = \frac{3.0931}{1 + exp(\frac{\nu + 12.1463}{-10})} \tag{A.6}$$

$$\tau_h = \frac{1}{\alpha_h + \beta_h} \tag{A.7}$$

$$h_{\infty} = \frac{\alpha_h}{\alpha_h + \beta_h} \tag{A.8}$$

$$I_{Na} = gmax \times m^3 \times h \times (V - E_{Na}) \tag{A.9}$$

#### Delayed rectifier potassium current

$$\alpha_n = -0.07 \times \frac{\nu + 8}{exp(\frac{\nu + 8}{-6}) - 1} \tag{A.10}$$

$$\beta_n = 0.264 \times exp(\frac{\nu + 33}{40}) \tag{A.11}$$

$$\tau_n = \frac{1}{\alpha_n + \beta_n} \tag{A.12}$$

$$n_{\infty} = \frac{\alpha_n}{\alpha_n + \beta_n} \tag{A.13}$$

$$I_K = gmax \times m^4 \times (V - E_K) \tag{A.14}$$

Quantitative simulation of extracellular single unit recording from the surface of cortex

**Table 1.** Electrical and Dimensional Properties for Finite Element Analysis.Electrical conductivities were attained from previous modeling studies [11, 49, 39, 64]

Domain	Conductivity (S $m^{-1}$ )	Radius/Size ( $\mu$ m)
Brain (Grey matter)	0.333	8,000
Cerebrospinal fluid	1.7857	8,500
Skull	6.25E-3	9,000
Scalp	0.43478	10,000
PEDOT:PSS	96,000	$10 \ge 10 \ge 10 \ge 10 \ \mu m^3$
GOLD	4.56 E7	$10 \ge 10 \ge 8 \ \mu m^3$
Parylene	1.6667 E- 15	$2 \ \mu m$ (thickness)

Quantitative simulation of extracellular single unit recording from the surface of cortex





Figure 1. Structure of the NEURON Models. (a) Layer 1 neurogliaform interneuron [26] (b) Layer 3 pyramidal cell [24] (c) Layer 5 pyramidal cell [23, 24] (d) Scalable neuron model derived from layer 5 pyramidal neuron.

Quantitative simulation of extracellular single unit recording from the surface of cortex



**Figure 2.** Layer 1 Neurogliaform Cell Transmembrane Currents. The somatic current had a 24 nA trough followed by a sharp 13 nA peak.

Quantitative simulation of extracellular single unit recording from the surface of cortex 24



Figure 3. Volume Conductor Model. (a) The finite element model of the rat head consisted of four spheres (grey matter, CSF, skull, and scalp) and the recording microelectrode described in Table 1. (b) Finite element mesh in which the node density was increased dramatically over the electrode and the immediately surrounding area using an adaptive physics controlled mesh defined in Comsol 5.2. C) Voltage distribution generated at the electrode and surrounding tissue from the 1 A current source.

Quantitative simulation of extracellular single unit recording from the surface of cortex

 
 Density neurons/mm<sup>3</sup>
 Radius (std) µm

 Layer 1
 9,830
 3.76 (1.04)

 Layer 2/3
 355,000
 5.31 (1.79)

 Layer 4
 213,000
 5.06 (1.60)

 Layer 5
 198,000
 4.77 (1.37)

Figure 4. Rodent Brain Histological Section. One of 73 NeuN-stained coronal sections of cortex. The density of neurons in each layer is indicated in neurons per volume and was calculated over at least 0.00542 mm3. The cortical layer thickness was confirmed by Buzsaki et al. 1998 [40] and Belgard et al. 2011 [41]. The radius of neurons in each layer were significantly different than each other (layer 1 and layer 5 p<0.05; layer 2/3 and layer 4 p<0.001). Scale bar = 100  $\mu$ m.

Quantitative simulation of extracellular single unit recording from the surface of cortex



**Figure 5.** Diagram of Various Neuron Sizes, Depths, and Recorded Spiking Activity. According to their respective layers, we placed the layer 1, 3, and 5 model neurons at various distances away from the 100  $\mu$ m<sup>2</sup> electrode contacts. To provide the optimal recording situation, we placed each neuron on the shallow end of their respective layer while preventing the neuron from extending past the edge of the brain. Axonal and dendritic recordings of layer 3 and 5 neurons never exceeded 1  $\mu$ V when the neuron was placed at the correct biological depth.

Quantitative simulation of extracellular single unit recording from the surface of cortex



**Figure 6.** Diagram of Simulated  $\mu$ ECoG Neural Recordings. Grid of three 100  $\mu$ m<sup>2</sup> electrodes on the surface of the brain with a layer 1 neurons at 20  $\mu$ m deep and 30  $\mu$ m deep. Inter electrode spacing of 30  $\mu$ m with insulation (parylene-c) surrounding the electrodes horizontally including a 4  $\mu$ m layer of insulation on the back.





Figure 7. Electrode Surface Area and Insulation's Effect on Recording Amplitude. The recordings originate from a layer 1 neuron 20  $\mu$ m away from the electrodes. (a) The black traces were recorded using a model with effectively an infinite amount of insulation on the four sides of the electrode and 2  $\mu$ m of insulation on the back of the electrode. The red traces were recorded using a model with no insulation on the electrodes. The electrodes' surface areas are: 0  $\mu$ m<sup>2</sup> (10<sup>-2</sup> represents a perfect electrode), 1  $\mu$ m<sup>2</sup>, 9  $\mu$ m<sup>2</sup>, 50  $\mu$ m<sup>2</sup>, 100  $\mu$ m<sup>2</sup>, 900  $\mu$ m<sup>2</sup>, 5000  $\mu$ m<sup>2</sup>, 10000  $\mu$ m<sup>2</sup>, 40000  $\mu$ m<sup>2</sup>, 90000  $\mu$ m<sup>2</sup>. (b) The amount of lateral insulation was varied on a 10 x 10  $\mu$ m<sup>2</sup> electrode, evaluated at .25  $\mu$ m<sup>2</sup>, 4  $\mu$ m<sup>2</sup>, 1000  $\mu$ m<sup>2</sup>, 577600  $\mu$ m<sup>2</sup>. (c) A comparison between the ideal model, where the electrode is perfectly adhered to the brain, and a more realistic recording environment, where 3.5  $\mu$ m of insulation was replaced with highly conductive CSF. The thin layer of CSF decreases the signal amplitude by 55%.



Figure 8. Scalable Model Validation and Neuron Size as it Relates to Voltage Spike Amplitude. The voltage trace of the scalable pyramidal neuron model compared to the layer 5 (a) and layer 3 (b) pyramidal neuron models [23, 24]. The scalable neuron was scaled to match the approximate soma size of both existing neuron models. The V<sub>pp</sub> was within 1% of the layer 5 model and 13% of the layer 3 model. (c) Voltage spike amplitude decreased approximately linearly with the surface area of the soma, but can be more accurately modeled as  $V_{\rm pp} = 0.6320 * exp(-0.8366 * ln[somaArea^{-1}])$ . The layer 5 pyramidal model, the layer 3 pyramidal model, and specific neuron sizes from the scalable model are indicated on the graph.

Quantitative simulation of extracellular single unit recording from the surface of cortex 30

#### References

- Viventi J, Kim DH, Vigeland L, Frechette ES, Blanco Ja, Kim YS, et al. Flexible, foldable, actively multiplexed, high-density electrode array for mapping brain activity in vivo. Nat Neurosci. 2011;14(12):1599–605.
- [2] Wray CD, Blakely TM, Poliachik SL, Ph D, Mcdaniel SS, Novotny EJ, et al. Multimodality Localization of the Sensorimotor Cortex in Pediatric Patients Undergoing Epilepsy Surgery. J Neurosurg Pediatr. 2012;10(0930908):1–6.
- [3] Rosin B, Slovik M, Mitelman R, Rivlin-Etzion M, Haber SN, Israel Z, et al. Closed-loop deep brain stimulation is superior in ameliorating parkinsonism. Neuron. 2011;72(2):370–384.
- [4] Schwartz AB. Cortical Neural Prosthetics. Annu Rev Neurosci. 2004;27:487–507.
- [5] Moxon KA, Foffani G. Brain-machine interfaces beyond neuroprosthetics. Neuron. 2015;86(1):55-67.
- [6] Schroeder KE, Chestek CA. Intracortical brain-machine interfaces advance sensorimotor neuroscience. Front Neurosci. 2016;10:1–8.
- [7] Nordhausen CT, Rousche PJ, Normann RA. Optimizing recording capabilities of the Utah Intracortical Electrode Array. Brain Res. 1994;637(1-2):27–36.
- [8] Tae Hwan Yoon, Eun Jung Hwang, Dong Yong Shin, Sek Ik Park, Seung Jae Oh, Sung Cherl Jung, et al. A micromachined silicon depth probe for multichannel neural recording. IEEE Trans Biomed Eng. 2000;47(8):1082–1087.
- [9] Vetter RJ, Williams JC, Hetke JF, Nunamaker EA, Kipke DR. Chronic neural recording using silicon-substrate microelectrode arrays implanted in cerebral cortex. IEEE Trans Biomed Eng. 2004;51(6):896–904.
- [10] Biran R, Martin DC, Tresco PA. Neuronal cell loss accompanies the brain tissue response to chronically implanted silicon microelectrode arrays. Exp Neurol. 2005;195(1):115–126.
- [11] Moffitt MA, McIntyre CC. Model-based analysis of cortical recording with silicon microelectrodes. Clin Neurophysiol. 2005;116(9):2240–2250.
- [12] Azemi E, Stauffer WR, Gostock MS, Lagenaur CF, Cui XT. Surface immobilization of neural adhesion molecule L1 for improving the biocompatibility of chronic neural probes: In vitro characterization. Acta Biomater. 2008;4(5):1208–1217.
- [13] Barrese JC, Rao N, Paroo K, Triebwasser C, Vargas-Irwin C, Franquemont L, et al. Failure mode analysis of silicon-based intracortical microelectrode arrays in non-human primates. J Neural Eng. 2013;10(6).

Quantitative simulation of extracellular single unit recording from the surface of cortex

- [14] Jorfi M, Skousen JL, Weder C, Capadona JR. Progress towards biocompatible intracortical microelectrodes for neural interfacing applications. J Neural Eng. 2015;12(1):011001.
- [15] Patel PR, Zhang H, Robbins MT, Nofar JB, Marshall SP, Kobylarek MJ, et al. Chronic in vivo stability assessment of carbon fiber microelectrode arrays. J Neural Eng. 2016;13(6):066002.
- [16] Luan L, Wei X, Zhao Z, Siegel JJ, Potnis O, Tuppen CA, et al. Ultraflexible nanoelectronic probes form reliable, glial scar-free neural integration. Science Advances. 2017;3(2):e1601966.
- [17] Skousen JL, Merriam SME, Srivannavit O, Perlin G, Wise KD, Tresco PA. Reducing surface area while maintaining implant penetrating profile lowers the brain foreign body response to chronically implanted planar silicon microelectrode arrays. In: J Schouenborg MG, Danielsen N, editors. Progress in Brain Research. vol. 194. 1st ed. Elsevier B.V.; 2011. p. 167–180.
- [18] Nguyen JK, Park DJ, Skousen JL, Hess-Dunning AE, Tyler DJ, Rowan SJ, et al. Mechanically-compliant intracortical implants reduce the neuroinflammatory response. J Neural Eng. 2014;11(5):056014.
- [19] Degenhart AD, Eles J, Dum R, Mischel JL, Smalianchuk I, Endler B, et al. Histological evaluation of a chronically implanted electrocorticographic electrode grid in a non-human primate. J Neural Eng. 2016;13(4):1–14.
- [20] Solovey G, Miller KJ, Ojemann JG, Magnasco MO, Cecchi GA. Self-Regulated Dynamical Criticality in Human ECoG. Front Integr Neurosci. 2012;6:44.
- [21] Holt GR, Koch C. Electrical interactions via the extracellular potential near cell bodies. J Comput Neurosci. 1999;6(2):169–184.
- [22] Khodagholy D, Gelinas JN, Thesen T, Doyle W, Malliaras GG, Buzsáki G. NeuroGrid: recording action potentials from the surface of the brain. Nature Neurosci. 2015;18(2):310– 315.
- [23] Mainen ZF, Joerges J, Huguenard JR, Sejnowski TJ. A model of spike initiation in neocortical pyramidal neurons. Neuron. 1995;15(6):1427–1439.
- [24] Mainen ZF, Sejnowski TJ. Influence of dendritic structure on firing pattern in model neocortical neurons. Nature. 1996;382(6589):363–366.
- [25] Cruikshank SJ, Ahmed OJ, Stevens TR, Patrick SL, Amalia N, Elmaleh M, et al. Thalamic control of layer 1 circuits in prefrontal cortex. J Neurosci. 2012;32(49):17813–17823.
- [26] Muralidhar S, Wang Y, Markram H. Synaptic and cellular organization of layer 1 of the developing rat somatosensory cortex. Front Neuroanat. 2014;7(52):1–17.

Quantitative simulation of extracellular single unit recording from the surface of cortex 32

- [27] Hines ML, Carnevale NT. NEURON : A Tool for Neuroscientists. Neuroscientist. 2001;7(2):123–135.
- [28] Hodgkin AL, Huxley AF. A quantitative description of membrane current and its application to conduction and excitation in nerve. Bull Math Biol. 1952;52(1-2):25–71.
- [29] Bezaire MJ, Raikov I, Burk K, Vyas D, Soltesz I. Interneuronal mechanisms of hippocampal theta oscillations in a full-scale model of the rodent CA1 circuit. eLife. 2016;5:1–106.
- [30] Prinz AA, Billimoria CP, Marder E. Alternative to hand-tuning conductance-based models: construction and analysis of databases of model neurons. J Neurophysiol. 2003;90(6):3998– 4015.
- [31] Van Geit W, De Schutter E, Achard P. Automated neuron model optimization techniques: A review. Biol Cybern. 2008;99(4-5):241–251.
- [32] Buzsáki G, Anastassiou Ca, Koch C. The origin of extracellular fields and currents-EEG, ECoG, LFP and spikes. Nature Rev Neurosci. 2012;13(6):407–20.
- [33] McIntyre CC, Richardson AG, Grill WM. Modeling the excitability of mammalian nerve fibers: influence of afterpotentials on the recovery cycle. J Neurophysiol. 2002;87(2):995– 1006.
- [34] Gold C, Henze DA, Koch C, Buzsáki G. On the Origin of the Extracellular Action Potential Waveform: A Modeling Study On the Origin of the Extracellular Action Potential Waveform: A Modeling Study. J Neurophysiol. 2006;95:3113–3128.
- [35] Hay E, Schurmann F, Markram H, Segev I. Preserving axosomatic spiking features despite diverse dendritic morphology. J Neurophysiol. 2013;109(12):2972–2981.
- [36] Larkman A, Mason A. Correlations between morphology and electrophysiology of pyramidal neurons in slices of rat visual cortex. I. Establishment of Cell Classes. J Neurosci. 1990;10(5):1415–28.
- [37] Rall W, Burke RE, Holmes WR, Jack JJB, Redman SJ, Segev I. Matching dendritic neuron models to experimental-data. Physiol Rev. 1992;72(4):S159–S186.
- [38] Sin K. Electrical stimulation of the spinal cord: a further analysis relating to anatomical factors and tissue properties. Med Biol Eng Comput. 1983;p. 264–269.
- [39] Slutzky MW, Jordan LR, Krieg T, Chen M, Mogul DJ, Miller LE. Optimal Spacing of Surface Electrode Arrays for Brain Machine Interface Applications. J Neural Eng. 2010;7(2):26004.
- [40] Mazzoni A, Lindén H, Cuntz H, Lansner A, Panzeri S, Einevoll GT. Computing the Local Field Potential (LFP) from Integrate-and-Fire Network Models. PLoS Comput Biol. 2015;11(12):1–38.

Quantitative simulation of extracellular single unit recording from the surface of cortex

- [41] Khodagholy D, Doublet T, Gurfinkel M, Quilichini P, Ismailova E, Leleux P, et al. Highly conformable conducting polymer electrodes for in vivo recordings. Adv Mater. 2011;23(36):268–272.
- [42] Lempka SF, Johnson MD, Moffitt MA, Otto KJ, Kipke DR, McIntyre CC. Theoretical analysis of intracortical microelectrode recordings. J Neural Eng. 2011;8(4):45006.
- [43] Gittins R, Harrison PJ. Neuronal density, size and shape in the human anterior cingulate cortex: A comparison of Nissl and NeuN staining. Brain Res Bull. 2004;63(2):155–160.
- [44] Schneider CA, Rasband WS, Eliceiri KW. NIH Image to ImageJ: 25 years of image analysis. Nature Methods. 2012;9(7):671–675.
- [45] Schindelin J, Arganda-Carreras I, Frise E, Kaynig V, Longair M, Pietzsch T, et al. Fiji: an open-source platform for biological-image analysis. Nature Methods. 2012;9(7):676–82.
- [46] Nowak K, Mix E, Gimsa J, Strauss U, Sriperumbudur KK, Benecke R, et al. Optimizing a Rodent Model of Parkinson's Disease for Exploring the Effects and Mechanisms of Deep Brain Stimulation. Parkinson's Disease. 2011;2011:1–19.
- [47] Yoshida Kozai TD, Langhals NB, Patel PR, Deng X, Zhang H, Smith KL, et al. Ultrasmall implantable composite microelectrodes with bioactive surfaces for chronic neural interfaces. Nature Materials. 2012;11(12):1065–1073.
- [48] Gilletti A, Muthuswamy J. Brain micromotion around implants in the rodent somatosensory cortex. J Neural Eng. 2006;3(3):189–195.
- [49] Wongsarnpigoon A, Grill WM. Computational modeling of epidural cortical stimulation. J Neural Eng. 2008;5(4):443–454.
- [50] Katzner S, Nauhaus I, Benucci A, Bonin V, Ringach DL, Carandini M. Local Origin of Field Potentials in Visual Cortex. Neuron. 2009;61(1):35–41.
- [51] Pesaran B. Uncovering the Mysterious Origins of Local Field Potentials. Neuron. 2009;61(1):1–2.
- [52] Markowitz JE, Liberti WA, Guitchounts G, Velho T, Lois C, Gardner TJ. Mesoscopic patterns of neural activity support songbird cortical sequences. PLoS Biology. 2015;13(6):1–20.
- [53] Mallet N, Schmidt R, Leventhal D, Chen F, Amer N, Boraud T, et al. Arkypallidal Cells Send a Stop Signal to Striatum. Neuron. 2016;89(2):308–316.
- [54] Robinson DA. The Eelectrical Properties of Metal Microelectrodes. Proc IEEE. 1968;56(6):1065–1071.
- [55] Moulin C, Glière A, Barbier D, Joucla S, Yvert B, Mailley P, et al. A New 3D Finite Element Model Based on Thin Film Approximation for Microelectrode Array Recording

Quantitative simulation of extracellular single unit recording from the surface of cortex 34 of Extracellular Action Potential. IEEE Trans Biomed Eng. 2006;55(c):683–692.

- [56] Kim DH, Viventi J, Amsden JJ, Xiao J, Vigeland L, Kim YS, et al. Dissolvable films of silk fibroin for ultrathin conformal bio-integrated electronics. Nature Materials. 2010;9(6):511– 517.
- [57] Malaga KA, Schroeder KE, Patel PR, Irwin ZT, Thompson DE, Bentley JN, et al. Datadriven model comparing the effects of glial scarring and interface interactions on chronic neural recordings in non-human primates. J Neural Eng. 2016;13(1):16010.
- [58] Fu TM, Hong G, Zhou T, Schuhmann TG, Viveros RD, Lieber CM. Stable long-term chronic brain mapping at the single-neuron level. Nature methods. 2016;13(10):875–82.
- [59] Plonsey R. Bioelectric phenomena. New York: McGraw-Hill; 1969.
- [60] Nelson MJ, Pouget P, Nilsen EA, Patten CD, Schall JD. Review of signal distortion through metal microelectrode recording circuits and filters. J Neurosci Methods. 2008;169(1):141– 157.
- [61] Stacey WC, Kellis S, Patel PR, Greger B, Butson CR. Signal distortion from microelectrodes in clinical EEG acquisition systems. J Neural Eng. 2012;9(5):056007.
- [62] Lempka SF, McIntyre CC. Theoretical Analysis of the Local Field Potential in Deep Brain Stimulation Applications. PLoS ONE. 2013;8(3).
- [63] Huigen E, Peper A, Grimbergen CA. Investigation into the origin of the noise of surface electrodes. Med Biol Eng Comput. 2002;40(3):332–338.
- [64] Kim YH, Sachse C, MacHala ML, May C, Müller-Meskamp L, Leo K. Highly conductive PEDOT:PSS electrode with optimized solvent and thermal post-treatment for ITO-free organic solar cells. Adv Funct Mater. 2011;21(6):1076–1081.