

PAPER • OPEN ACCESS

RETRACTED: RNN based prediction of spatiotemporal data mining

To cite this article: Mohammed Ali Shaik *et al* 2020 *IOP Conf. Ser.: Mater. Sci. Eng.* **981** 022027

View the [article online](#) for updates and enhancements.

You may also like

- [Research Progress of Spatio-Temporal Interpolation in the Field of Public Health](#)
Xin Liu, Fujun Wang and Zhijie Zhang
- [Spatiotemporal Dengue Disease Clustering by Means Local Spatiotemporal Moran's Index](#)
I G N M Jaya, Y Andriyana, B Tantular et al.
- [Resonance and frequency-locking phenomena in spatially extended phytoplankton–zooplankton system with additive noise and periodic forces](#)
Quan-Xing Liu, Zhen Jin and Bai-Lian Li



ECS
The
Electrochemical
Society
Advancing solid state &
electrochemical science & technology

DISCOVER
how sustainability
intersects with
electrochemistry & solid
state science research

Retraction

Retraction: RNN based prediction of spatiotemporal data mining (*IOP Conf. Ser.: Mater. Sci. Eng.* **981** 022027)

Published 15 February 2023

This article has been retracted by IOP Publishing following an allegation that this article may contain tortured phrases [1].

IOP Publishing has investigated and agrees the article contains a number of nonsensical phrases that feature throughout the paper to the extent that the article makes very little sense. This casts serious doubt over the legitimacy of the article and the expertise of the authors in this topic.

IOP Publishing wishes to credit PubPeer commenters [2] for bringing the issue to our attention.

The authors neither agree nor disagree to this retraction.

[1] Cabanac G, Labbe C, Magazinov A, 2021, arXiv:2107.06751v1

[2] <https://pubpeer.com/publications/EB7C68106400A4BD1BA7093DB1F0DA#>

Retraction published: 15 February 2023



Content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](https://creativecommons.org/licenses/by/3.0/). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

Published under licence by IOP Publishing Ltd

RNN based prediction of spatiotemporal data mining

Mohammed Ali Shaik¹, Dhanraj Verma², P Praveen³, K Ranganath⁴, Bonthala Prabhajan Yadav⁵

^{1,3}Department of Computer Science & Engineering, SR University, Warangal, Telangana, India

²Professor, Department of Computer Science & Engineering, Dr. APJ Abdul Kalam University, Indore, India

^{4,5}Sumathi Reddy Institute of Technology for Women, Warangal, India

Email: niharali@gmail.com

Abstract. The Spatiotemporal pattern is considered by most of the researchers to be a rehashed arrangement or relationship of specific occasions or highlights of spatiotemporal and to distinguish these groupings or affiliations are related to the spatiotemporal patterns of wrongdoing events and proper separation are clearly based on length based estimations that are expected to oblige the size or state of the pattern and ST patterns comprises of various sizes and shapes after some time are non-consistently disseminate over space by performing analytical learning of spatiotemporal successions as it is capable of creating future pictures by knowledge from the authentic edges. Spatial advents and temporal varieties are two pivotal structures which are considered in this paper which proposes the predictive methodology which utilizes recurrent neural network where the approach of persistent neural networks stands apart as a suitable worldview for without model as the data is based on the prediction of nonlinear dynamical frameworks by applying the methodology in Spatiotemporal pattern which predicts the limited mistake.

Keywords: Data Mining, Spatiotemporal, Machine Learning, Prediction and Recurrent Neural Network

1. Introduction

A Spatio-temporal data has gotten broad in a few applications like general wellbeing, open security, money related misrepresentation recognition, transportation, climate anticipating, etc. A Spatiotemporal database involves the basic varieties in space and time. Not at all like the conventional dataset are ceaseless, unfathomable and it has a time variation data dispersion as it is a troublesome and complex errand to find the fascinating patterns from this database. In this manner the proficient data mining method, for example, bunching and arrangement are utilized for tackling the above issues. Data mining is the way toward separating the noteworthy patterns from the datasets to remove the data and it changes into a necessary structure for some time later.

A multi esteemed choice frameworks approach was created in [1] for deciding the Spatio-temporal patterns from the time arrangement data as right now the unpleasant set hypothesis was applied to pick the significant highlights from the dataset and the exact bunching was not done to discover the Spatio-temporal patterns with less blunder rate. The spatiotemporal object is an object with at any rate one spatial data along with the single sequential property and the spatial attributes are the aspects of



position and geometry with respect to existence of an object and the sequential property is based on interim time where the aspirant object is substantial along with characteristics such as spatial or sequential or non sequential when considered [2,26].

Spatiotemporal datasets gather the changing estimations of spatial and topical traits after some time period based on the occasion in spatiotemporal dataset clarifies the spatial and temporal wonder at time 'T' and location 'P' as the spatiotemporal data mining is an examination zone for advancement and for investigation of the huge spatiotemporal databases.

The patterns with the varieties in spatial attributes with respect to time aspect is named as the spatiotemporal patterns which performs the data digging as the undertakings are utilized for deciding various sorts of conceivably valuable and obscure patterns from the spatiotemporal databases and the patterns and patterns are utilized for spatiotemporal marvels and dynamic or pre-preparing step for investigation and mining [3,27].

Spatiotemporal data contains the conditions of object based on occasion or position in space after some time period as enormous measure of spatiotemporal data is gathered from application fields like traffic the board then condition observing and climate conjecture. Spatiotemporal data are utilized in numerous fields like ecological sciences, geophysics, oceanography, soil science, econometrics, the study of disease transmission, natural science, ranger service, picture handling. The marvels of intrigue are constant in space and time as the data are accumulated with time and space and the plenty of strategy like environmental contamination focuses on precipitation fields and surface breezes are arranged through the spatial and temporal variability. Utilizing the forecast in explicit pieces of our advancement lead is basic to different applications and fills various requirements it is easy for foresee advancement on different levels. On a critical level, flexibility expectation is for example basic to choose bottlenecks in transportation structures and plan reasonable transportation establishment [4] and to provide operational guidance in a disaster conditions [5,28,29] or to distinguish possibly dangerous cutting-edge events.

On this level forecast models generally dismiss individual moving substances as the model amassed surges of people changing beginning with a one area then onto the following or along certain transportation sections. The objective for anticipating the territory or zone or point of convergence an individual is most likely going to visit at some point or another. Laudable use cases for such expectation fuse territory based proposition structures [6,30] which ought to have the alternative to helpful prompt someone about significant imminent offers or near to POIs. With extending self-administration of transport system, these models will most likely increment further essentialness, as they can be used to redistribute resources subject to the gauge convey ability demands in explicit areas.

Expectation is a critical endeavor while performing the "spatiotemporal data mining" [12,32] as the expectation of tasks that occur while implementing the explicit physical territories is considerably huge in a couple of utilization spaces and the examples of issues which require region expectation consolidate bad behavior examination where the cell organizes and disastrous occasions such as: flames or floods or droughts or ailments or seismic tremors as the region and also physical attributes for striving temporal object that comprises of dynamic characteristics for a given specific span of time with variant characteristics that updates themselves constantly [31].

2. Literature review

Mal-Sarkar et al [7,35] Discovering epic and appealing spatio temporal model in sensor data is an imperative test in various intelligent regions and similar data are every now and again perpetual or unbounded and related with quick time variety dissemination with neighborhood [16,33] and spatial patterns as this paper represents a procedure that joins an enlargement of customary disagreeable set construing framework to prevent the space time variety data streams [9,34] as the possibility of multivalued resultant structures has been implemented to speak to different prototypes in a particular time span or visualizing such patterns or designs are implemented in undesirable set based rule acknowledgment process [8,17,36].

The framework for sensor data joining is spoken to by utilizing a space time that gathers the instrument sought after by the period of formats along with the neighborhood rules from related packs as the multi valued assessment system licenses mining dense patterns as an alternate to the single motivation in a provided organization instead of having a need of complex part change as it empowers us to calculate and check the probable data pressure that is related to vulnerability parameters [10]. Ultimately all the results are endorsed and further differentiated with other related algorithms as the framework will empower us to appreciate and concealed by considering the "part and whole" or spatio temporal metrological association instead of giving up the semantics with respect to the attributes of sensor data [11,38].

Urner et al [8, 18]. Locate the following spot forecast as the AI techniques which consolidate relevant data are every now and again utilized because the previous examinations frequently don't permit determining universal methodological proposals as they utilize diverse datasets and strategies for separating space or sizes of expectation by implementing the forecast algorithms and setting data as per the need equivalence[18,37]. The virus start issue for new clients is an issue based on the investigation which anticipates the next spots dependent on one direction dataset however with deliberately fluctuating forecast algorithms and techniques for space separating based on sizes of expectation and joined setting data. This process permits to assess the general impact of these variables on the general expectation precision for handling the virus start issue predominant in recommender and expectation frameworks to test the impact of preparing the indicator on all clients rather than every individual one [19,40].

Rashid, et al [9,39] investigation the spatiotemporal database (STDB) [22,41] has gotten impressive consideration during the previous couple of years, because of the rise of various applications (e.g., flight control frameworks, climate estimate, mobile figuring, and so on.) that demand proficient administration of moving articles [20,43]. These applications record items' geographical areas (sometimes additionally shapes) at different timestamps and bolster inquiries that investigate their verifiable and future (prescient) practices [21,42]. The STDB altogether expands the customary spatial database that manages just stationary information and subsequently is inapplicable to moving articles whose dynamic conduct requires re-examination of various subjects including information displaying by performing the related question calculations as many of the application performs immense measures of information are produced unequivocally or verifiably containing spatial or spatiotemporal information as the capacity to break down these information stays lacking and the requirement for adjusted information mining instruments turns into a noteworthy test [23,46].

S. Kisilevich et al [10,45] Spatiotemporal clustering is a procedure of collection items dependent on their spatial and worldly closeness as it is moderately new subfield of information mining which increased high ubiquity particularly in geographic information sciences because of the inescapability of a wide range of area based or environmental gadgets that record position or time or environmental properties of an article or set of items continuously [24,44]. There exists many sorts and a lot of spatiotemporal information wound up accessible that acquaint new difficulties with information examination and require novel ways to deal with learning revelation by focusing on the spatiotemporal clustering in geographic space [28,47]. We initiate the process by characterizing distinct sorts of spatiotemporal information by identifying the center point around one kind of spatiotemporal clustering direction clustering which provides the diagram by cutting edge methodologies and strategies for spatiotemporal clustering and at last present a few situations in various application areas to perform environmental investigations [27].

Ganesan Pillai et al [11] locate the spatiotemporal co happening examples speak to subsets of occasion types that happen together in both realities and in contrast with past effort in this field that extant a general structure to distinguish spatiotemporal occurring examples for persistently developing spatiotemporal occasions that have polygon like portrayals [25]. We likewise propose a lot of events to recognize spatiotemporal happening designs and propose an Apriori based spatiotemporal occurrence mining calculation to discover pervasive spatiotemporal happening designs for broadened spatial portrayals that develop after some time as we assess our system on genuine information to exhibit the

adequacy of our measures and the calculation and present outcomes featuring the significance of our measures in distinguishing spatiotemporal co-event designs [26].

3. Problem statement

The spatiotemporal predictive learning issue is to predict the most likely length. Prediction is a significant undertaking in spatio-temporal data mining. Here the likelihood of occasions happening at specific environmental areas is significant in a few application spaces. Spatio-temporal procedures are regularly high-dimensional, displaying muddled changeability crosswise over reality. Customary state space model ways to deal with such procedures within the sight of dubious data have been demonstrated to be valuable. In any case, estimation of state-space models in this setting is frequently tricky since parameter vectors and frameworks are of high measurement and can have entangled reliance structures. On the other hand, one can consider the spatio-temporal issue from a multivariate geostatistical point of view which requires spacetime covariance capacities be indicated. Generally, this methodology has been restricted in that the known class of substantial spatio-temporal covariance capacities is very little, in spite of the fact that as of late, a few creators have broadened this class of capacities.

4. Proposed Method

In this paper we proposed an efficient prediction approaches for spatio-temporal mining using machine learning approach.

4.1. Extracting spatiotemporal data

Spatial prediction is worried about the expectation of the event, amount and additionally condition of land marvels, typically dependent on preparing of data for performing the ground estimations or tests $\sum_{n=1}^i Y * (s_i)$ where s_i belongs to D which is a spatial facilitate with n is the quantity of watched areas where the D represents geological area and temporal expectation that attains the results and further represented using the gridded maps when there should be an occurrence of space time forecast that is enlivened perceptions of spatiotemporal expectations.

The “expectation procedure as it prompts straight limits in the subsequent guide which are straightforwardly identified with the design of the examining plan by indicating the exactness depicts the proportion between the quantities of accurately anticipated and the absolute number of tests on account of the picked AI approaches”. In request to build up a model with solid match the data extraction must be viably caught as the data is chronicled exclusively for investigation purposes in this way as a rule having huge number of occurrences to work with.

In any case of most spatio-temporal application total data from various sources which results in moderately littler dataset to complete data mining tasks as the data model created ought to have the option to catch the non-straight connection between the different factors [13]. These incorporate the connections between the information factors with the variable itself at various focuses in time and the communication between the spatially scattered factors.

4.2. Pre-processing

Spatiotemporal data, the event of a data occasion is firmly obliged or subject to the idea of the occasion in the neighbouring unit and the past example of a similar occasion as the data models bring about high residuals in light of the fact that the spatial connections between the properties isn't fittingly caught. The direction data are unevenly examined and could contain an extensive stretch of missing data as obvious that the data is tried with harsh holes and it is presumably last 3 to 4 days missing data [14]. Needful for various following circumstances and the choice pace of development could vary from seconds to third days as the data could be tried and assembled each 3–5 days [29]. For vehicles the probable examining rate could be as little as seconds and for the larger portion of following mining approaches expect the data is reliably tried and the straightforward and as often as possible utilized for initially handling step is to utilize direct access to make the data reliably gapped [28].

4.3. Prediction using recurrent neural networks

A type of neural networks [14] are better known as “Recurrent Neural Networks (RNN)” [15] has displayed exceptionally perfect execution in demonstrating temporal structures and the interjection calculations. Numerical outcomes exhibit that our proposed RNN outflanks [30] solid benchmark models including profound feed forward neural networks. Recurrent Neural Networks, which are talented in arrangement handling, is successful for the errand as it has become a well known pattern to abuse RNNs related to the “Convolutional Neural Networks (CNNs)” [31] for request prediction and attributable to the capacity of CNNs to mine spatial relationships and the endeavours are likewise made to exclusively use CNNs or its variations.

“Recurrent neural System (RNS)” [32] is a variety of feed forward neural system (FNS) [33]: FNS includes layers stacked more than one another as all the independent layer comprises of neurons as the whole associations between distinct layers are preceded by the similar course as it brings cyclic structure into the system which is executed without anyone else association of neurons and further utilizes by self associated neurons that posses verifiable information sources can be remembered by RNS and along these lines impact the system yield as the memory that holds the RNN empowers it to beat FNS in some genuine applications as the induction procedure of RNS is like that of FNN [32] which is done by forward engendering[36].

Preparing the process of FNS is finished by implementing the algorithm “Back Proliferation (BP)” [34] which is based on the RNS procedure that arranges or initializes the data which has the potential to perform exchange of data available in memory into consideration as this manner the preparation procedure must stack the BP results after some span of time all the measurements bringing about the “Back Spread Through Time (BPTT)” [35] algorithm for a fundamental RNS organization made out of initial information layer with probable i neurons as the probable shrouded layer with the probable h neurons with a single acquiesce layer with k neurons as it advances the back spreads are as beneath because contribution of the system which is the succession X over the length T which forwards the engendering process adopted as:

$$a_h^t = \sum_{i=1}^I w_{ih} * x_i^t + \sum_{h'=1}^H w_{h'h} * b_{h'}^{t-1} \quad (1)$$

$$b_h^t = \phi_h(a_h^t) \quad (2)$$

$$a_k^t = \sum_{h=1}^H w_{hk} * b_h^t \quad (3)$$

Where X_i^t is the estimation of i^{th} measurement on time step t , w_{ij} indicates the probable weights between neurons i, j as the input which is taken to implement the activation function over j^{th} neuron at the t^{th} timestep is further represented as a_j^t and b_j^t then further ϕ_h speaks to the actuation capacity of neuron h with utilization of “BPTT algorithm” over RNN is illustrated in equation 4 and 5 as:

$$\delta_j^t = \frac{\delta L}{\delta a_j^t} \quad (4)$$

$$\delta_h^t = \phi'(\sum_{k=1}^K w_{hk} * \delta_k^t + \sum_{h'=1}^H w_{h'h} * \delta_{h'}^{t+1}) \quad (5)$$

In the above equations L denotes loss function and δ_j^t is the angle of misfortune work over contribution of neuron j at time step t and for waking the figuring the slopes and loads in the system are refreshed by angle drop algorithm as the RNN design comprises of a three dimensional heap of neural systems NN_{ij}^k , where i and j are the typical spatial directions of the contact guide and k is a “temporal” file.

Algorithm: Spatio temporal RNN

Step 1: Start

Step 2: Partition Edges in a graph GR , $CE = \{\sum_m^1 Edge\}$

Step 3: generate factor components, $G = \psi_{vp}, \psi_{em}$

Step 4: identify each vertex ψ_{vp} with RNN R_{vp}

Step 5: identify each edge ψ_{em} with RNN R_{em}

Step 6: in a bipartite graph connect $= \sum_m^1 \psi_{vp}$ with $\sum_m^1 \psi_{em}$

Step 7: ψ_{vp} and $\psi_{em} \in E_R$ if there exists vertex vp and $u \in$ to vertex $SD(u, v) \in \psi_{em}$

Step 8: return $grap = ((\psi_{em} * \psi_{vp}), E_r)$

Step 9: Stop

All the neural systems in the stack have a similar topology (same info, covered up, and yield layer sizes) with a solitary concealed layer, and a solitary sigmoidal yield unit assessing the likelihood of contact among I and j at the level k . Moreover, right now, the systems in the level k have similar loads (weight sharing).


Each level k can be prepared in a completely directed manner, utilizing a similar contact maps as targets. Along these lines, each degree of the profound engineering speaks to a particular contact predictor[50].

The contributions to NN_{ij}^k can be isolated into simply spatial data sources, and temporal information sources (which are not absolutely temporal but rather incorporate additionally a spatial part). For fixed i and j because they possess simply spatial information sources are indistinguishable for all levels k in the stack henceforth they don't rely upon "time". These absolutely spatial sources of info incorporate developmental profiles that perform prediction over auxiliary structure and dissolvable openness in a window around residue i and residue j as these are the standard data sources utilized by most predictors which attempt to predict[51].

Inspiration for this work depends on an absence of generalizable bits of knowledge about the overall impact of various model viewpoints similarly the prediction calculation over the scale of prediction with the melded setting data and the space discretization technique on the prediction exactness[52].

5. Experimental result

We conduct experimental results and that were shown in this section where our motivation for this work depends on an absence of generalizable experiences about the overall impact of various model viewpoints for performing the prediction calculation at a scale of prediction the melded setting data and the space discretization method on the prediction exactness[53]. This is a result of the path that there is by and by a nonattendance of concentrates which are commensurate as in they give some degree of spread similarly as the used course dataset or other key viewpoints where the guideline responsibility of our work is the assessment of different showing draws near, the prediction exactness at different spatial objectives (which we join by methods for our novel dynamic model depicted previously) and the effect of various spatio-temporal features on the prediction[49].



We look at the exhibition of the subsequent models to a few pattern indicators to decide the precision picks up that can be come to by applying AI techniques to enormous datasets of exact development data. And we find that depending upon the spatial scale of the anticipated spots either raster or bundle based strategies will when all is said in done yield a higher precision and that spatial and temporal setting features change in their effect at different spatial objectives moreover. We in like manner find that the proposed model achieves a prediction exactness of around 75%, which displays its propriety to customer unequivocal models that are similar to the fundamentally better introduction stood out from the standard indicators[48].

5.1. Data

The GoEco! Is further “evaluated whether mobile applications that comprises of lively components and has the potential to impact the portability conduct of individuals for performing the investigation around 700 clients were followed over the term of a half year in with their day by day developments and transport mode decisions were recorded at a normal goal of one TrackPoint each 541 m which is extraordinarily relies upon the picked method of transport and for performing strolling exercises the following goals is a lot higher when compared with the application spares when the probable patterns change while strolling”.




Figure 2. Pattern discovery




Figure 3. Prediction accuracy

5.2. Predictor accuracy

Our proposed strategy to perform prediction is sensibly well and accomplish around 10% higher exactness than the best estimate model.

The best predictor accuracy attained is 75.5% which is further “accomplished when utilizing a RNN in mix with an area input, trailed by the presentation of an arbitrary timberland model with input as the predictor accuracy can be separated to each degree of the progressive system as exhibited in graph 3 and the prediction framework is various leveled that follows the spot which should be predicted effectively at each level to accomplish a right by and large prediction or to attain the prediction accuracy on each level separately using the Recurrent neural network performs superior to the irregular backwoods as a rule”.

6. Conclusion

Spatiotemporal data includes the conditions of object, occasion or position in space after some time period. Enormous measure of spatiotemporal data is gathered from application fields like traffic the board, condition checking and climate estimate. Utilizing prediction, in specific parts of our development conduct is critical to various applications and fills different needs. One can predict development on various levels. This paper proposed a predictive methodology of Spatio-temporal utilizing recurrent neural network. From this we accomplish nonexistence of generalizable bits of knowledge about the overall impact of various model perspectives for example the prediction calculation with certain scale of prediction that is performed over the fused setting data and the space discretization strategy on the prediction accuracy.

7. References

- [1] C. C. Aggarwal and C. Zhai, 2012 Mining Text Data
- [2] M. Kepa, J. Szymanski 2015 Two stage SVM and kNN text documents classifier *In: Pattern Recognition and Machine Intelligence, Kryszkiewicz M. (Ed.), Lecture Notes in Computer Science* Vol. 9124 pp. 279 -289
- [3] R. C. Barik and B. Naik 2015 A Novel Extraction and Classification Technique for Machine Learning using Time Series and Statistical Approach *Computational Intelligence in Data Mining* vol. 3 pp. 217-228
- [4] Ali Shaik M 2020 Time series forecasting using vector quantization *Int J Adv Sci Technol* vol 29(4) pp169-175
- [5] R. Bruni and G. Bianchi 2015 Effective Classification Using a Small Training Set Based on Discretization and Statistical Analysis *IEEE Trans. Knowl. Data Eng.*, vol. 27(9) pp 2349-2361
- [6] A. Chaudhuri 2014 Modified fuzzy support vector machine for credit approval classification *IOS Press and Authors* vol. 27(2) pp 189-211
- [7] E. Baralis, L. Cagliero, and P. Garza 2013 EnBay: A novel pattern-based Bayesian classifier *Tkde* vol. 25(12) pp 2780-2795
- [8] X. Fang 2013 Inference-Based Naive Bayes: Turning Naive Bayes Cost-Sensitive vol. 25(10) pp 2302-2314
- [9] C. H. Wan, L. H. Lee, R. Rajkumar, and D. Isa 2012 A hybrid text classification approach with low dependency on parameter by integrating K-nearest neighbor and support vector machine *Expert Syst. Appl* vol. 39(15) pp 11880 -11888
- [10] L. H. Lee, R. Rajkumar, and D. Isa, "Automatic folder allocation system using Bayesian-support vector machines hybrid classification approach," *Appl. Intell.*, vol. 36, no. 2, pp. 295-307, 2012.
- [11] M. Parchami, B. Akhtar, and M. Dezfoulian 2012 Persian text classification based on K-NN using wordnet *Adv. Res. Appl* vol 7345 pp 283-291
- [12] Mohammed Ali Shaik, P. Praveen 2020 A Survey On Various Clustering Algorithms Using Nature Inspired Algorithms *Journal Of Mechanics Of Continua And Mathematical Sciences*

Vol 15(7) pp 282-293

- [13] M. Wang H. Zhang, and R. Ding 2011 Research of text categorization based on SVM *International Conference on Infomatics, Cybermetics and Computer Engineering ICCE* Vol. 2 pp 69-77
- [14] K. Lin, and M. Chen 2011 On the Design and Analysis of the privacy-preserving SVM classifier *IEEE Trans. Knowl. Data Eng.*, vol 23(11) pp 1704-1717
- [15] Z. Liu, X. Lv, K. Liu, and S. Shi 2010 Study on SVM compared with the other text classification methods *2nd Int. Work. Educ. Technol. Comput. Sci. ETCS* vol. 1 pp. 219-222
- [16] Mohammed Ali Shaik 2020 Time Series Forecasting using Vector quantization *International Journal of Advanced Science and Technology (IJAST)* Vol 29(4) pp 169-175
- [17] H. Cheng, P. Tan, and R. Jin 2010 Efficient algorithm for localized support vector machine *Knowl. Data Eng.* vol 22(4) pp 537-549
- [18] W. Zhang, T. Yoshida, and X. Tang 2008 Text classification based on multi-word with support vector machine *Knowledge-Based Syst.*, vol. 21(8) pp 879-886
- [19] C. Burges 1998 A Tutorial on Support Vector Machines for Pattern Recognition *Data Min. Knowl. Discov.* vol 2(2) pp 121-167
- [20] R. Ravi Kumar, M. Babu Reddy and P. Praveen 2017 A review of feature subset selection on unsupervised learning *Third International Conference on Advances in Electrical, Electronics, Information, Communication and Bio-Informatics (AEEICB)*, pp163-167
- [21] P.Praveen, B.Rama 2019 An Efficient Smart Search Using R Tree on Spatial Data *Journal of Advanced Research in Dynamical and Control Systems* vol 4 pp1943-1949.
- [22] P. Praveen, B. Rama and T. Sampath Kumar 2017An efficient clustering algorithm of minimum Spanning Tree *Third International Conference on Advances in Electrical, Electronics, Information, Communication and Bio-Informatics (AEEICB)* pp 131-135
- [23] Shaik,M.A 2019 A Survey on Text Classification methods through Machine Learning Methods *International Journal of Control and Automation (IJCA)* vol 12(6) pp 390-396
- [24] P. Praveen and B. Rama 2016 An empirical comparison of Clustering using hierarchical methods and K-means *International Conference on Advances in Electrical, Electronics, Information, Communication and Bio-Informatics (AEEICB)* pp.445-449
- [25] Sallauddin Mohmmad , G. Sunil , Ranganath Kanakam 2017 A Survey On New Approaches Of Internet Of Things *Data Mining International Journal of Advanced Research in Computer Science* vol 8(8) pp 123-135
- [26] Sallauddin Mohmmad, Dr.M.Sheshikala, Shabana 2018 Software Defined Security (SDSec):Reliable centralized security system to decentralized applications in SDN and their challenges *Jour of Adv Research in Dynamical & Control Systems* Vol 10(10) pp 147-152
- [27] Sallauddin Mohmmad, Shabana , Ranganath Kanakam 2017 Provisioning Elasticity On IoT's Data In Shared-Nothing Nodes *International Journal of Pure and Applied Mathematics* vol 117(7) pp 165-173
- [28] Mohammed Ali Shaik 2019 Time Series Data Prediction Methods for Mining Temporal Data *Accent Journal of Economics Ecology & Engineering* Vol 4(5) pp 123-128.
- [29] Shaik, M.A, T.Sampath Kumar 2019 Research on Multi-Agent Experiment in Clustering *International Journal of Recent Technology and Engineering (IJRTE)* vol 8(1S4) pp. 1126-1129
- [30] Mohammed Ali Shaik, P.Praveen, Dr.R.Vijaya Prakash 2019Novel Classification Scheme for Multi Agents *Asian Journal of Computer Science and Technology* vol.8(S3) pp. 54-58
- [31] Mohammed Ali Shaik, S Narsimha Rao, Abdul Rahim 2013a Survey Of Time Series Data Prediction On Shopping Mall *Indian Journal of Computer Science and Engineering (IJCSE)*vol. 4(2) pp 174-184
- [32] T. Sampath Kumar,B. Manjula, D. Srinivas 2017 A New Technique to Secure Data Over Cloud *Jour of Adv Research in Dynamical & Control Systems* vol 11 pp 145-149
- [33] T. Sampath Kumar, B. Manjula, Mohammed Ali Shaik, Dr. P. Praveen2019 A Comprehensive

- Study on Single Sign on Technique *International Journal of Advanced Science and Technology (IJAST)* Vol-127 pp 156-162
- [34] Dr.Seena Naik 2016 An Effective use of Data Mining Techniques to Creation *International Journal Of Advancement In Engineering* vol 3(10) pp 157-163
- [35] D.Ramesh, Syed Nawaz Pasha, G.Roopaa 2017 A Comparative Analysis of Classification Algorithms on Weather Dataset Using Data Mining Tool *Oriental Journal of Computer Science and Technology* vol 10(4) pp1-5
- [36] Chythanya KR, Kumar KS, Rajesh M, Tharun Reddy S 2020 Sensor Cloud: A Breakdown information on the Utilization of Wireless Sensor Network by Means of Cloud Computing *Test Eng Manage* vol 82 pp13945-13954
- [37] Shaik MA. 2019 A survey on text classification methods through machine learning methods *Int J Control Autom* vol 12(6) pp 390-396
- [38] Chanti Y, Raman K, Seenanaik K, Mahesh D, Bhaskar B. 2019 An enhanced on bidirectional li-fi attocell access point slicing and virtualization using das2 *Int J Recent Technol Eng* vol 8(Special Issue 3) pp 1109-1120
- [39] Kothandaraman D, Sheshikala M, Seena Naik K, Chanti Y, Vijaykumar B. 2019 Design of an optimized multicast routing algorithm for internet of things *Int J Recent Technol Eng* vol 8(2) pp 4048-4053
- [40] Pramod Kumar P, Sandeep CH, Naresh Kumar S 2018 An overview of the factors affecting handovers and effective highlights of handover techniques for next generation wireless networks *Indian J Public Health Res Dev* vol 9(11) pp 722-725
- [41] Harshavardhan A, Babu S, Venugopal T 2017 Brain tumor segmentation methods-a survey *J Adv Res Dyn Control Syst* vol 9(11) pp 240-245
- [42] Naresh Kumar S, Pramod Kumar P, Sandeep C, Thirupathi V, Shwetha S 2019 A study on deep Q-learning and single stream Q-network architecture *Int J Adv Sci Technol* vol 28(20) pp 586-592
- [43] Kumar RR, Reddy MB, Praveen P. 2019 Text classification performance analysis on machine learning *Int J Adv Sci Technol* vol 28(20) pp 691-697
- [44] Ravi Kumar R, Babu Reddy M, Praveen P 2019 An evaluation of feature selection algorithms in machine learning *Int J Sci Technol Res* vol 8(12) pp 2071-2074
- [45] Jamalpur, Bhavana 2020 Data Exploration As A Process Of Knowledge Finding And The Role Of Mining Data Towards Information Security *Journal Of Mechanics Of Continua And Mathematical Sciences* vol 15(6) pp 2020-2028
- [46] Jamalpur Bhavana, Komuravelly Sudheer Kumar 2019 Implementation of Bovw Model Towards Obtaining Discriminative Features of the Images *International Journal of Advanced Science and Technology* vol 28(17) pp 205-213
- [47] J.Bhavana, Komuravelly Sudheer Kumar 2019 A Study on the Enhanced Approach of Data Mining Towards Providing Security for Cloud Computing *Indian Journal of Public Health Research & Development* vol 9(11) pp 225-232
- [48] Harshavardhan A, Suresh Babu Dr and Venugopal T Dr 2016 “3D Surface Measurement through Easy-snap Phase Shift Fringe Projection”, *Springer conference International Conference on Advanced Computing and Intelligent Engineering Proceedings of ICACIE* **1** 179-186
- [49] Harshavardhan A, Suresh Babu and Dr, Venugopal T Dr 2017 “An Improved Brain Tumor Segmentation Method from MRI Brain Images” *2017 2nd International Conference On Emerging Computation and Information Technologies (ICECIT)* IEEE 1–7. DOI.org (Crossref) doi:10.1109/ICECIT.2017.8453435.
- [50] A.Harshavardhan Syed Nawaz Pasha Sallauddin MD D.Ramesh 2019 “Techniques used for clustering data and integrating cluster analysis within mathematical programming” *journal of mechanics of continua and mathematical sciences* **14(6)** 546-57, DOI.org (Crossref)https://doi.org/10.26782/jmcms.2019.12.00038

- [51] Mahender K, Ramesh KS and Kumar TA 2017 An efficient ofdm system with reduced papr for combating multipath fading *Journal of Advanced Research in Dynamical and Control Systems* 9(Special issue 14) 1939-1948
- [52] Rajasri I, Gupta AVSSKS and Rao YVD 2014 Symmetry and its Effects on Structures of Planetary Gear Trains *Journal of The Institution of Engineers (India): Series C* 95(1) 77-81 10.1007/s40032-014-0101-9
- [53] Seena Naik K and Sudarshan E 2019 Smart healthcare monitoring system using raspberry Pi on IoT platform ARPJ Journal of Engineering and Applied Sciences 14(4) 872-876.

Retracted